

FEL-PRO, INCORPORATED -- FEL-PRO C-300 AEROSOL 7W79221 -- 8030-00-111-6266

=====  
Product Identification  
=====

Product ID:FEL-PRO C-300 AEROSOL 7W79221

MSDS Date:03/14/1986

FSC:8030

NIIN:00-111-6266

MSDS Number: BBGKC

=== Responsible Party ===

Company Name:FEL-PRO, INCORPORATED

Address:7450 N. MCCORMICK BLVD.

City:SKOKIE

State:IL

ZIP:60076

Info Phone Num:(312) 674-7700

Emergency Phone Num:(312) 67

4-7700

CAGE:KO111

=== Contractor Identification ===

Company Name:FEL-PRO INC DIV OF FELT PRODUCTS MFG CO

Address:7450 N MCCORMICK

Box:1103

City:SKOKIE

State:IL

ZIP:60076-4046

Country:US

Phone:847-674-7700 OR 312-761-4500

CAGE:73165

Company Name:FEL-PRO, INCORPORATED

Address:7450 N. MCCORMICK BLVD.

City:SKOKIE

State:IL

ZIP:60076

Phone:(312) 674-7700

CAGE:KO111

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CA

S:71-55-6  
RTECS #:KJ2975000  
Fraction by Wt: 56%  
Other REC Limits:350 PPM (CL)  
OSHA PEL:350 PPM/450 STEL  
ACGIH TLV:350 PPM/450STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 7.4%  
Other REC Limits:400 PPM  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:DIPROPYLENE GLYCOL METHYL ETHER  
CAS:34590-94-8  
RTECS #:JM1575000  
Fraction by Wt: 2.4%  
Other REC Limits:100  
PPM  
OSHA PEL:S,100PPM/150STEL  
ACGIH TLV:S,100PPM/150STEL9192

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 1.5%  
Other REC Limits:100 PPM  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 9.3%  
Other REC Limits:1800 MG/CUM  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE, 2-METHYLPROPANE  
CAS:75-28-5  
RTECS #:TZ4300000  
Fraction by Wt: 5.7%  
O

ther REC Limits:1000 PPM  
OSHA PEL:1800 MG/CUM  
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: MAY RESULT IN DIZZINESS,  
HEADACHE, & NAUSEA. EYE/SKIN: IRRITATION, REDNESS, & SENSITIVE.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:INHALATION: DIZZINESS, HEADACHES, & NAUSEA.  
SKIN/EYES  
: IRRITATION, REDNESS, & SENSITIVITY.  
Medical Cond Aggravated by Exposure:SENSITIVITY

===== First Aid Measures =====

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN:  
WASH THOROUGHLY W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR.  
GIVE CPR OR OXYGEN IF NEEDED. INGESTION: OBTAIN MEDICAL ATTENTION  
IF REQUIRED .

===== Fire Fighting Measures =====

Flash Point:NO FLASHBACK  
Lower Limits:0.8%  
Upper Limits:10.5%  
Extinguishing Media:CO2, FOAM, DRY CHEMICAL. WATER MAY BE INEFFECTIVE  
Fire Fighting Procedures:WATER MAY BE USED TO COOL FIRE EXPOSED  
CONTAINER.  
Unusual Fire/Explosion Hazard:CANS WILL RUPTURE FROM INTERNAL PRESSURE  
AT 190F AND DISCHARGE CONTENTS. TOXIC FUMES FROM DECOMPOS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. VENTILATE AREA.  
WIPE UP WITH RAGS. USE CHLORINATED SOLVENT OR HIGH-FLASH POINT  
CLEANER TO COMPLETE CLEANUP.

===== Handling and Storage =====

Handling and Storage Precautions:NORMAL HANDLING AND STORAGE. DO NOT  
STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND  
PROTECTED FOR STORAGE OF NFPA CLASS IA LIQ.  
Other Precautions:DO NOT INGEST. DO NOT SPRAY IN EYES. DO NOT PUNCTURE  
OR INCINERATE CAN. DO NOT STICK PINS OR NAILS INTO OPENING AT TOP  
OF CAN KEEP OUT OF REACH OF CHILDREN.

===== Exposure C

ontrols/Personal Protection =====

Respiratory Protection:NONE NEEDED WITH ADEQUATE VENTILATION  
Ventilation:LOCAL EXHAUST: PREFERRABLE (50 PPM). MECHANICAL: ACCEPTABLE (50 PPM),  
Protective Gloves:RECOMMENDED  
Eye Protection:SAFETY GLASSES, GOGGLES  
Other Protective Equipment:OPTIONAL  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3  
Spec Gravity:1.36  
Evaporation Rate & Reference:SOLVENTS FLASH OFF  
Solubility in Water:NIL  
Appearance and Odor:DARK GREY COATING, SOLVENT ODOR  
Percent Volatiles by Volume:90%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS, PEROXIDES, PERMANGANATES  
Stability Condition to Avoid:FUMES >750F  
Hazardous Decomposition Products:CO, CO2, HYDROCARBON FUMES, POSSIBLE SULFUR OXIDES,

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS A COMBUSTIBLE SOLID IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility

for the suitability of this information to their particular situation.