

DELTA PETROLEUM CO.,INC. -- MIL-L-2105C; -- 9150-00-001-9395

=====  
Product Identification  
=====

Product ID:MIL-L-2105C;

MSDS Date:01/01/1987

FSC:9150

NIIN:00-001-9395

MSDS Number: BCTXM

=== Responsible Party ===

Company Name:DELTA PETROLEUM CO.,INC.

Emergency Phone Num:504-833-2861

CAGE:7A348

=== Contractor Identification ===

Company Name:DELTA PETROLEUM CO., INC

Address:10352 RIVER ROAD,

Box:103

97

City:ST. ROSE

State:LA

ZIP:70087

Country:US

Phone:504-832-2732

CAGE:7A348

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LUBRICATING OIL BASE (TAKE TLV AS OIL MIST)

ACGIH TLV:5MG/CUM(OILMIST)

Ingred Name:ADDITIVES (CONTAINS ABOUT 5% SULFUR,PHOSPHORUS & TRACES OF METAL SALTS)

ACGIH TLV:NOT SPECIFIED

=====  
Hazards Identification  
=====

Effects of Overexposure:LOW ORDER OF TOXICITY AND IRRITANCY PER MFR;MAY IRRITATE E

YES,SKIN AND RESPIRATORY TRACT.

=====  
First Aid Measures  
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF

NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH;

GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER

SYMPTOMS OF OVEREXPOSURE.

=====  
Fire Fighting Measures  
=====

Flash Point:329F/165C (COC)

Extinguishing Media:FOAM,DRY CHEMICAL,WATERSPRAY,WATERFOG,CO\*2.

Fire Fightin

g Procedures:USE NIOSH/MSHA APPROVED SCBA IN CONFINED AREA.  
Unusual Fire/Explosion Hazard:DO NOT USE DIRECT STREAM OF WATER. USE  
REASONABLE CARE.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE  
ABSORBENT MATERIALS AND RECOVER IT FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED  
AREA.K

KEEP AWAY FROM HEAT,OPEN FLAMES AND STRONG OXIDIZING  
AGENT.KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES.DO NOT USE  
CONTAMINATED CLOTHES.DO NOT BREATHE VAPORS OR MIST;WASH THOROUGHLY  
AFTER EACH USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED SCBA OR RESPIRATOR FOR  
ORG.VAPORS/MIST (>TLV

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE  
VENTILATION

Pro

ective Gloves:NEOPRENE

Eye Protection:GOGGLES

Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE  
WASH STATION

Supplemental Safety and Health

MSDS UNDATED

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:500F/260C

Vapor Pres:1.0

Spec Gravity:0.900

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID,ODOR MILD

Percent Volatiles by Volume:NEGL

===== Stability and

Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: DO NOT HEAT ABOVE 50C FOR LONG PERIODS.

Hazardous Decomposition Products: CO AND/OR CO\*2, P, S. ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.