View NSN Online: https://aerobasegroup.kr/nsn/6850-00-003-5295

CHEMTRONICS INC -- CLEANING AND LUBRICATING COMPOUND -- 6850-00-003-5295

Product ID:CLEANING AND LUBRICATING COMPOUND MSDS Date:09/18/1990 FSC:6850 NIIN:00-003-5295 MSDS Number: BCTYQ === Responsible Party === **Company Name: CHEMTRONICS INC** Address:8125 COBB CENTER DRIVE City:KENNESAW State:GA ZIP:30144 Country:US Info Phone Num:404-424-4888 FAX 404-424-4267 Emerg ency Phone Num:404-424-4888/800-424-9300(CHEMTREC) Preparer's Name: MICHAEL WATKINS CAGE:2M589 === Contractor Identification === Company Name: CHEMTRONICS INC Address:8125 COBB CENTER DRIVE Box:City:KENNESAW State:GA ZIP:30152 Country:US Phone:770-424-4888/800-645-5244 CAGE:21267 Company Name: CHEMTRONICS INC (CANCELLED USE 21267) City:HAUPPAUGE State:NY ZIP:11760 Country:US CAGE:2M589 Company Name: MALTER INTERNATIONAL BULK CHEMICAL DIVISION Address:80 FIRST STREET Box:City:GRETNA State:LA ZIP:7005

3 Country:US Phone:504-362-3232, OR 800-535-4095 CAGE:27978

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III) CAS:76-13-1 RTECS #:KJ4000000 Fraction by Wt: 97% Other REC Limits:NONE SPECIFIED OSHA PEL:1000PPM/1250STEL ACGIH TLV:1000PPM/1250STEL9192 Ozone Depleting Chemical:1

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III) CAS:75-71-8 RTECS #:PA8200000 Fraction by Wt: 35% Other REC Limits:NONE SPEC IFIED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1

Ingred Name:SILICON FLUID CAS:63148-62-9 RTECS #:JT6485000 Fraction by Wt: 5% Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >10,000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:PRODUC T IS IRRITATING TO BODY TISSUES, IT IS A CENTRAL NERVOUS SYSTEM DEPRESSANT, CAUSING NAUSEA AND DIZZINESS. CHRONIC SKIN EXPOSURE MAY CAUSE DERMATITIS. IT HAS A LOW TOXICITY. Explanation of Carcinogenicity: THE PRODUCT CONTAINS NO INGREDIENT THAT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN. Effects of Overexposure: HEADACHE, DIZZINESS, DROWSINESS, NAUSEA, STUPOR OR DULLNESS, LETHARGY AND DRUNKENNESS. VERY HIGH CONCENTRATIONS MAY LEAD TO UNCONSCIOUSNESS OR EVEN DEATH IN CON FINED OR POORLY VENTILATED AREAS. REPEA TED SKIN CONTAC CAUSES REDDNESS. EYE CONTACT CAUSES DISCOMFORT. Medical Cond Aggravated by Exposure:CARDIOVASCULSR DISEASE. First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. INHALED: REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:D O NOT INDUCE VOMITING. GIVE 2 LAR GE GLASSES OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE, SEE A DOCTOR. Flash Point:NON-FLAMMABLE Extinguishing Media: PRODUCT IS NON FLAMMABLE. EXTINGUISH FIRE WITH

MEDIA APPROPRIATE FOR SOURCE OF FIRE.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE.

**USE WATER** 

SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE! EXPOSURE TO TEMPERATURES OVER 130 F MAY RESULT IN RUPTURE OF THE CONTAINER.

Spill Release Procedures:SMALL SPILL: WIPE UP WITH RAGS OR TOWELS. VENTILATE AREA. RESIDUE WILL EVAPORATE QUICKLY. DO NOT FLUSH TO SEWER OR WATERWAY. Neutralizing Agent:NONE

=================== Handling and Storage ==

Handling and Storage Precautions: STORE BELOW 130 F. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE. DEPRESSURIZE BEFORE DISPOSAL. ROTATE STOCK. Other Precautions: VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS. DO NOT ENTER WHERE VAPORS ARE SUSPECTED WITHOUT SELF CONTAINED BREATHING APPARATUS AND AN OBSERVER. Respiratory Protection: USE NIOSH/MSHA APPROVED AIR SUPPLIED RES PIRATOR OR RESPIRATOR FOR ORGANIC VAPOR IF EXPOSURE IS ABOVE THE TLV/PEL. IF EXPOSED ABOVE 1000 PPM USE ONLY A SUPPLIED AIR RESPIRATOR. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE Ventilation:NORMAL ROOM VENTILATION IS SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST IF PEL/TLV IS EXCEEDED. Protective Gloves: NEOPRENE, PVA GLOVES RECOMMENDED. Eye Protection: SAFETY GLASSES OR SPLASH GOGGLES Other Protective Equipment: APRON AND WORK CLOTHING TO MINIMIZE EXPOSURE. EYE WASH STATION & SAFETY SHOWER RECOMMENDED.

Work Hygienic Practices: USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

**CHEMICAL NAME &** 

SYNONYMS-DICHLORODIFLUOROMETHANE-TRICHLOROTRIFLUOROETHANE;POLY(DIME THYL) SILOXANE

## HCC:V2

NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:118F,48C Vapor Pres:334 MM Vapor Density:6.5 Spec G ravity:1.57 Evaporation Rate & amp; Reference:>1 (N-BUTYL ACETATE = 1) Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS LIQUID, SOLVENT ODOR Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES ALKALI AND ALKALINE EARTH METALS, POWDERED REACTIVE METALS SUCH AS AL, ZN. BE. STRONG BASES Stability Condition to Avoid:SPRAYING NEAR FLAME OR HOT SURFACES Hazardous Decomposition Products:WHEN INV

## OLVED IN FIRE, PRODUCT EMITS TOXIC AND IRRITATING FUMES OF HYDROGEN CHLORIDE, HYDROGEN FLUORIDE & CARBONYL HALIDE

Waste Disposal Methods:DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL REGULATIONS. DO NOT PUNCTURE OR INCINERATE AEROSOL CANS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Ame rica in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.