

ESSEX CHEM.CORP.SPECIALTY CHEM.DIV. -- PRO-SEAL 870 B-2(ACCELERATOR) --
8030-00-008-7200

===== Product Identification =====

Product ID:PRO-SEAL 870 B-2(ACCELERATOR)

MSDS Date:01/01/1985

FSC:8030

NIIN:00-008-7200

Kit Part:Y

MSDS Number: BCVDL

=== Responsible Party ===

Company Name:ESSEX CHEM.CORP.SPECIALTY CHEM.DIV.

Emergency Phone Num:213-537-7600

CAGE:JO802

=== Contractor Identification ===

Comp

any Name:ESSEX CHEM.CORP.SPECIALTY CHEM.DIV.

CAGE:JO802

Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

Phone:310-537-7600

CAGE:83527

===== Composition/Information on Ingredients =====

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: UNK

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:MANGANESE DIOXIDE (AS MANGANESE)

CAS:1313-13-9

RTECS #:OP0350000

Fractio

n by Wt: UNK
OSHA PEL:C,5 MG/M3/1 FUME TWA
ACGIH TLV:5 MG/M3 DUST/1 FUME

Ingred Name:PLASTICIZER(AROMATIC PLASTICIZER)
Fraction by Wt: UNK

=====
Hazards Identification
=====

Effects of Overexposure:ACUTE:NONE KNOWN. CHRONIC:AFFECTS CNS.

=====
First Aid Measures
=====

First Aid:EYE:IMMEDIATELY FLUSH W/WATER AT LEAST 15 MINUTES TO REMOVE
PARTICLES. CALL MD. SKIN:WASH W/SOAP & WATER.

=====
Fire Fighting Measures
=====

Flash Point:>230F TCC
Extinguishing Media:FOAM, CO*2, WATER
Unusual Fire/Explosion Hazard:MODERATE, BY CHEMICAL REACTION:OXIDIZER.

=====
Accidental Release Measures
=====

Spill Release Procedures:MFR SUGGESTS COLLECT W/SWEEPING COMPOUND AND
REACT W/BASE COMPOUND.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE BELOW 80F. AVOID PROLONGED
HIGHER TEMPERATURES.

=====
Exposure Controls/Personal Protection
=====

Protective Gloves:NEOPRENE
Eye Protection:SAFETY SHIELD GOGGLES.
Supplemental Safety and Health
MFR GIVES ORAL: LD50(RAT)14.9 G/KG. PRODUCT CONFORMS TO MIL-S-81733
TYPE II-2. PART B OF A 2 PART PRODUCT. KEY1:N1.

=====
Physical/Chemical Properties
=====

HCC:N1
Boiling Pt:B.P. Text:645F
Spec Gravity:2.0
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK SLURRY-ODORLESS
Percent Volatiles

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
DO NOT HEAT W/EASILY OXIDIZABLE MATERIAL.

===== Disposal Considerations =====

Waste Disposal Methods: MFR SUGGESTS REACT W/BASE COMPONENT AND DISPOSE AS INERT MATERIAL. DISPOSE IAW LOCAL, STATE AND FED REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.