

DEXTER HYSOL AEROSPACE INC;THE DEXTER CORPORATION -- EA 934 PART A --  
8040-00-016-8662

=====  
Product Identification  
=====

Product ID:EA 934 PART A

MSDS Date:01/01/1987

FSC:8040

NIIN:00-016-8662

Kit Part:Y

MSDS Number: BCVJX

=== Responsible Party ===

Company Name:DEXTER HYSOL AEROSPACE INC;THE DEXTER CORPORATION

Emergency Phone Num:415 687 4201

CAGE:33564

=== Contractor Identification ===

Company

Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TRIGLYCIDYL P-AMINOPHENOL,EPOXY RESIN,CAS#5026-74-4

Fraction by Wt: 35.0%

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Fraction by Wt: 14.0%

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9192

Ingred Name:UNIDENTIFIED COMPO

NENTS

Fraction by Wt: 51.0%

ACGIH TLV:NOT SPECIFIED

===== Hazards Identification =====

Effects of Overexposure:SKIN:MAY IRRITATE & POSSIBLE ALLERGIC REACTION;  
PROLONGED & REPEATED CONTACT MAY CAUSE SENSITIZATN

===== First Aid Measures =====

First Aid:EYES/SKIN:FLUSH W/PLENTY OF WATER; WASH SKIN THOROUGHLY  
W/SOAP & WATER,RUBBING ALCOHOL OR HAND CLEANER. DO NOT USE  
SOLVENTS; REMOVE SOILED CLOTHING & WASH BEFORE  
REUSE. IF IRRITATION  
PERSISTS OR INCREASES, SEE A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:>300F/149C (EST)  
Extinguishing Media:DRY CHEMICALS,WATER SPRAY OR FOG, FOAM  
Fire Fighting Procedures:WEAR SELF-CONTND.BRTHNG APPART(SCBA)FIRE  
FIGHTNG CONF. SPACE  
Unusual Fire/Explosion Hazard:DENSE SMOKE & TOXIC GASES MAY BE  
LIBERATED FROM HEAT OF FIRE.

===== Accidental Release Measures =====

Spill Release Proc  
cedures:WEAR PROTECTIVE CLOTHING,GLOVES, & SAFETY  
GLASSES; SCRAPE UP & TRANSFER TO METAL CONTAINER-WIPE UP REMAINING  
RESIDUE W/SOLVENTS,OBSERVING SOLVENT FLAMMABILITY CAUTIONS, OR USE  
DETERGENT

===== Handling and Storage =====

Handling and Storage Precautions:KEEP PRODUCT COOL IAW LABEL  
INSTRUCTIONS;DO NOT HEAT MIXED ADHESIVE ABOVE 125F UNLESS CURING  
SURFACES TO BE BONDED; OBSERVE CAUTIONS FOR HEAT BUILD-UP  
Other Precautions:FOLLOW RECOMMEN

DED CURING SCHEDULE.DO NOT HEAT MIXED  
ADHESIVE (>125F); FAILURE TO OBSERVE CAUTIONS MAY RESULT IN  
EXCESSIVE HEAT BUILD-UP WITH RELEASE OF TOXIC GASES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPRVD MASK FOR TOXIC DUSTS WHEN CURED  
PRODUCT DRY SANDED,ETC.

Ventilation:LOCAL EXHAUST: RECOMMENDED WHEN SANDING CURED  
PRODUCT;MECHAN

Protective Gloves:IMPERVIOUS TYPE

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment

:AS NEEDED TO PROTECT SKIN & CLOTHING

Supplemental Safety and Health

MSDS DATED:JAN 10,1986.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:DECOMPOSES

Vapor Pres:1.0

Evaporation Rate & Reference:NIL

Solubility in Water:NIL

Appearance and Odor:VISCIOUS GREY PASTE WITH SLIGHT ODOR

Percent Volatiles by Volume:~1 LB. TOTAL

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS A HAZARDOUS WASTE

IAW TO DOT

HAZARD CLASS; IF ITEM DOES NOT MEET ANOTHER CLASS,DISPOSE OF AS  
ORM-E;DISPOSAL METHOD CAN BE LAND BURIAL OR CHEMICAL INCINERATION  
AAS REGULATED BY ALL GOVERN MENTAL AGENCIES;

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liabili

ty for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.