

EASTMAN KODAK COMPANY -- KODAK FIXER WASH SYSTEM CLEANER -- 6750-00-037-9099

=====
Product Identification
=====

Product ID:KODAK FIXER WASH SYSTEM CLEANER

MSDS Date:08/02/1989

FSC:6750

NIIN:00-037-9099

MSDS Number: BCVVS

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:

716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
Composition/Information on Ingredients
=====

Ingred Name:SODIUM SESQUICARBONATE

CAS:533-96-0

RTECS #:FG2092000

Fraction by Wt: 90-95%

Ingred Name:ETHYLENEDIAMINETETRAACETIC ACID SODIUM SALT

CAS:64-02-8

RTECS #:AH5075000

Fraction by Wt:

5-10%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALE: LOW HAZARD FOR RECOMMENDED
HANDLING. SKIN: LOW HAZARD FOR RECOMMENDED HANDLING. EYES: LOW
HAZARD FOR RECOMMENDED HANDLING. INGEST: EXPECTED TO BE A LOW
INGESTION HAZARD.
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IARC, NT
P, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR FOLLOWING OVEREXPOSURE. EYES:
FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN.
SKIN: WASH AFTER EACH CONTACT. INGESTION: IF SWALLOWED DRINK 1-2
GLASSES O F WATER. SEEK MEDICAL ATTENTION.

=====
===== Fire Figh
ting Measures =====

Flash Point:NONCOMBUSTIBLE
Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF
WATER.
Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling and Storage =====

Handling and Stora

ge Precautions:NONE.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED DUST RESPIRATOR IF VENTILATION IS INADEQUATE.

Ventilation:MECHANICAL(GENERAL)/LOCAL EXHAUST IF NECESSARY.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEMICAL/SAFETY GOGGLES

Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

s =====

HCC:N1

Vapor Pres:NEGLIGIBLE

Spec Gravity:>1.0

Evaporation Rate & Reference:NEGLI.(N-BUTYL ACETATE=1)

Solubility in Water:APPRECIABLE

Appearance and Odor:COLORLESS POWDER, ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH THE MATERIAL MAY REASONABLY COME IN CONTACT.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Deco

mposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate

and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.