

WOLF'S HEAD OIL REFINING CORPORATION -- H.D.ALL PURPOSE GEAR LUBE SAE 140 --  
9150-00-056-9523

===== Product Identification =====

Product ID:H.D.ALL PURPOSE GEAR LUBE SAE 140

MSDS Date:01/01/1985

FSC:9150

NIIN:00-056-9523

MSDS Number: BCWLB

=== Responsible Party ===

Company Name:WOLF'S HEAD OIL REFINING CORPORATION

Emergency Phone Num:814-677-6198

CAGE:DO762

=== Contractor Identification ===

Compa

ny Name:PENNZOIL CO

Address:700 MILIAM PENNZOIL PL

Box:2967

City:HOUSTON

State:TX

ZIP:77252-2967

Country:US

Phone:800-546-6227

CAGE:01326

Company Name:WOLF'S HEAD OIL COMPANY

Address:P.O.BOX 808

Box:808

City:OIL CITY

State:PA

ZIP:16301-0808

Phone:713-236-6070

CAGE:DO762

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON LUBRICANT

===== Hazards Identification =====

Effects of Overexposure:SKIN: PRLNG EXPOS-D

ERMAT INHAL:

MIST/FUMES-ASPIRATION PNEUMONIA. INGEST: NAUS, LAXATIVE, EYE: IRRIT.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH W/ WARM WATER, IF LIQ IS HOT-TREAT FOR BURNS,SEE MD. SKIN: WASH W/ SOAP& WATER. HOT LIQ MAY CAUSE SEVERE BURNS. FO BURNS: CHILL AREA,TREAT FOR SHOCK, SEE MD. INHAL: REMOVE TO FRESH AIR IMM ED. IF BREATH STOPS GIVE ARTF RESP SEE SUPP DATA

=====  
Fire Fighting Measures  
=====

Flash Point:550F; 288C (COC)  
Extinguishing Media:FOAM, DRY CHEM, CO\*2  
Fire Fighting Procedures:DO NOT USE STREAM OF H\*2O CAUSES FROTHING & SPREADS FIRE.  
Unusual Fire/Explosion Hazard:CO AND SOOT CAN BE PRODUCED IN AN OXYGEN DEFICIENT FIRE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SMALL SPILLS: PICK UP W/ ABSORBENTS. LARGE SPILLS: USE PUMPS,BUCKETS,SHOVELS,OR OTHER APPLICABLE TOOLS. PUT DRY SAND OR SPECIAL OIL ABSORBENT ON OILY AREAS TO HELP PREVENT ACCIDENTS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE AS A FLAMMABLE AND COMBUSTIBLE LIQUID. RESP PROTECTION: DO NOT USE COMPRESSED OXYGEN IN HYDROCARBON ATMOSPHERES.  
Other Precautions:WASH THOROUGHLY AFTER HANDLING. CONSUMPTION OF FOOD & BEVERAGES IS PROHIBITED IN AREAS WHERE HYDROCARBONS ARE PRESENT. DO NOT TRANSFER TO UNMARKED CONTAINERS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:MFR RECOMNDS NIOSH/MSHA APPRVD RESPIRATOR FOR PARTICULAR EXPOSURE.  
Ventilation:SUFFICIENT VENT TO KEEP BELOW TLV.  
Protective Gloves:INSULATED  
Eye Protection:SAFETY GOG/FACE SHIELD  
Other Protective Equipment:PLASTIC OR RUBBERIZED PERSONAL PROTECTIVE EQUIPMENT.  
Supplemental Safety and Health  
FIRST AID PROCEDURES: INGEST: DO NOT INDUCE VOMITING, CALL MD. BOILING PT: (MIDPOINT) >1000F;538C. CONTAINER SIZE: 120 LB DRUM

=====

Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:SEE SUP DTA

Spec Gravity:0.901

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, DARK RED MILD SULFUR ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECOMMENDS CO

NTROLLED INCINERATION OR

SANITARY LANDFILL. DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND  
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this

document should seek competent profes

sional advice to verify and

assume responsibility for the suitability of this information to their  
particular situation.