

TRIRAM CORP -- PR50-AF, TT-C-498B, COATING CMPD -- 8030-00-058-6795

=====  
Product Identification  
=====

Product ID:PR50-AF, TT-C-498B, COATING CMPD

MSDS Date:01/01/1985

FSC:8030

NIIN:00-058-6795

MSDS Number: BCWNF

=== Responsible Party ===

Company Name:TRIRAM CORP

Emergency Phone Num:617-875-6600

CAGE:59983

=== Contractor Identification ===

Company Name:TRIRAM CORP

Address:721 WAVERLY ST

Box:642

Ci

ty:FRAMINGHAM

State:MA

ZIP:01701-8512

Country:US

CAGE:59983

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:ALUMINUM PIGMENT, % APPROX

Fraction by Wt: 11%.

Ingred Name:ASPHALT, % APPROX

RTECS #:SE7350000

Fraction by Wt: 68%

ACGIH TLV:5MG/CUM, FUMES

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Fraction by Wt: 10%

OSHA PEL:0.2 FIBERS/CC

ACGIH

TLV:2 FIBERS/CC; A1;9192

Ingred Name:ADDITIVES  
Fraction by Wt: 1%

=====  
Hazards Identification  
=====

Effects of Overexposure:MFR STATES SAME AS ANY PETROLEUM DERIVATIVE

=====  
First Aid Measures  
=====

First Aid:EYE: IMMED FLUSH W/WATER AT LEAST 15 MIN, CALL MD. SKIN: WASH THOROUGHLY AFTER HANDLING.

=====  
Fire Fighting Measures  
=====

Flash Point:124F COC

Extinguishing Media:CO\*2, F  
OAM, SAND

Fire Fighting Procedures:SIMILAR TO OTHER PETROLEUM PROD

Unusual Fire/Explosion Hazard:NONE, SIMILAR TO OTHER PETROLEUM PROD

=====  
Accidental Release Measures  
=====

Spill Release Procedures:DRY W/NORMAL GARAGE FLOOR CLEANER, I E SPEEDY OIL DRY. MFR SUGGESTS USING MINERAL SPIRITS OR KEROSENE ON DRIED MATL TAKING PRECAUTIONS AGAINST FIRE & INH HAZ.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:  
AVOID EXCESSIVE HEAT OR MOISTURE

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROT IF NEC

Ventilation:LOCAL EXHST, YES

Protective Gloves:IF NEC

Eye Protection:GOGGLES IF NEC

Other Protective Equipment:AS REQ

Supplemental Safety and Health

ADDRESS: TRIRAM CORP. 721 WAVERLY ST. FRAMINGHAM, MA 01701.

=====  
Physical/Chemical Properties  
=====

HCC:V4

Boiling Pt:B.P. Text:313F

Spec Gravity:1.04

Evaporat

ion Rate & Reference:0.06

Appearance and Odor:SILVER COLOR, ODOR SIMILAR TO MINERAL SPIRITS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW LOCAL, STATE, FED REG

Disclaimer (provided with this information by the compiling agencies):

Th

is information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.