View NSN Online: https://aerobasegroup.kr/nsn/5970-00-061-1974

Product ID:PT-107 MSDS Date:01/01/1985 FSC:5970 NIIN:00-061-1974 **MSDS Number: BCWSG** === Responsible Party === Company Name: PRODUCTS/TECHNIQUES, INC. Address:3271 S RIVERSIDE AVE City:RIALTO State:CA ZIP:92316 Country:US Emergency Phone Num:909-877-3951 CAGE:06341 === Contractor Identification === **Company Nam** e:PRODUCTS/TECHNIQUES INC Address:3271 S RIVERSIDE AVE Box:City:RIALTO State:CA ZIP:92376 Country:US Phone:909-877-3951 CAGE:06341

Ingred Name:SALICYLANILIDE; CAS #871-72-0 RTECS #:VN8750000 Fraction by Wt: 3.45% ACGIH TLV:500PPM(PER MFR)

Ingred Name:FLAMMABLE LIQUIDS(TYPE NOT SPECIFIED) Fraction by Wt: 96.5%

Effects of Overexposure:HEADACHE, NAUSEA, MODE

RATELY	IRRITATING	ТΟ	<b>EYES</b>
& SKIN	l.		

======================================
First Aid:REMOVE VICTIM FROM VAPORS, RESTORE BREATHING IF NECESSARY. REMOVE FROM SKIN WITH SOAP & WATER. FLUSH EYES WITH PLENTY OF WATER.
======================================
Flash Point:82F TCC Lower Limits:1.1 Extinguishing Media:CO*2, FOAM OR DRY CHEMICAL. Fire Fighting Procedures:DO NOT USE WATER. Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE BETWEEN UPPER & LOWER EXPLOSIVE LIMITS.
======================================
Spill Release Procedures:REMOVE SOURCES OF IGNITION, APPLY SAWDUST OR OTHER ABSORBENT MATERIAL. KEEP MATERIAL FROM SPREADING.
======================================
Handling and Storage Precautions:FLAMMABLE,STORE AWAY FROM OPEN FLAME & HIGH HEAT. Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT WITH
SKIN.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:FOR CONFINED AREAS USE BUREAU OF MINES RESPIRATORY DEVICE. Ventilation:AS REQUIRED TO CONTROL LEL IN AIR.
Protective Gloves:RUBBER
Eye Protection:SAFETY GOGGLES Other Protective Equipment:RUBBER SOLES,BM2304 CART;BM23-12 FILTERS,BM-23-13 FILTERCUPS Supplemental Safety and Health
======================================
HCC:E3

HCC:F3 Boiling Pt:=107.2C, 225.F B.P. Text:225-3 00F Appearance and Odor:LIQUID Percent Volatiles by Volume:52.7

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Hazardous Decomposition Products:CO, CO\*2, ALDEHYDES & OTHER ORGANICS.

Waste Disposal Methods:PUT IN APPROVED METAL CONTAINER & SEAL FOR DISPOSAL & SHIP TO AN APPROVED DISPOSAL AREA.

Disclaimer (provided with this information by t he compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.