

EASTMAN CHEMICAL PRODUCTS,INC. -- EASTMAN ETHYL ACETATE, 85% -- 6810-00-062-6954
===== Product Identification =====

Product ID:EASTMAN ETHYL ACETATE, 85%

MSDS Date:01/01/1987

FSC:6810

NIIN:00-062-6954

MSDS Number: BCWTY

=== Responsible Party ===

Company Name:EASTMAN CHEMICAL PRODUCTS,INC.

Address:WILCOX DR AND LINCOLN ST

Box:431

City:KINGSPORT

State:TN

ZIP:37662

Country:US

Emergency Phone Num:615

-229-2000

Preparer's Name:NOT PROVIDED

CAGE:78364

=== Contractor Identification ===

Company Name:CANCELLED WITHOUT REPLACEMENT (WAS SNYDER, GEO H INC)

Box:431

Phone:NONE

CAGE:78364

Company Name:EASTMAN CHEM PRODUCTS A SUB OF EASTMAN KODAK CO

Address:EASTMAN ROAD

Box:City:KINGSPORT

State:TN

ZIP:37662

Country:US

Phone:423-229-2000

CAGE:74364

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 85

%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 15%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

=====
===== Hazards Identification =====

Effects of Overexposure:VAPOR CAUSES UPPER RESPIR.TRACT
IRRITA;LIQ/VAPOR CAUSES EYE IRRIT;ALSO SKIN DRYING,CRACKING.

=====
===== First Aid Measures =====

First Aid:INH:REMOVE F
ROM EXPOSURE.TREAT SYMTOMATICALLY,GET MED ATTN;
EYE:ANY MATL IN EYES SHOULD BE WASHED OUT IMMEDIATELY & MED ATTN IF
SYMPTONS PERSIST.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=-2.6C, 27.F
Autoignition Temp:=465.6C, 870.F
Lower Limits:2.05
Upper Limits:9.3
Extinguishing Media:SM:CO*2, DRY CHEM. LG:H*2O SPRAY,FOG OR FOAM
Fire Fighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD
BRTHG APP.
Unusual Fire/Explosi
on Hazard:WATER MAY BE INEFFECTIVE FOR FIRE
FIGHTING;VAPORS ARE HEAVIER THAN AIR & MAY TRAVEL FAR,FLASH BACK.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES.SMALL SPILLS
MAY BE COLLECTED WITH ABSORBENT MATL. FOR LARGE SPILLS,FLUSH AREA
WITH WATER SPRAY.PREVENT RUNOFF FROM ENTERING DRAINS,SEWERS OR
STREAMS.

=====
===== Handling and Storage =====

Handling and Storage Precau

tions:STORE IN COOL,DRY WELL VENTED,LOW FIRE
RISK AREA. PROTECT FR HEAT,SHOCK KEEP CONTAINERS CLOSED.
Other Precautions:SINCE EMPTIED PACKAGES RETAIN PRODUCT RESIDUE,FOLLOW
LABEL WARNINGS EVEN AFTER PACKAGE IS EMPTIED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MESA APPR SCBA/AIR SUPP RESPIR.
Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED
Protective Gloves:RECOMMENDED
Eye Protection:SAFETY GLASSES
Other Protecti
ve Equipment:SAFETY SHOWER & EYE BATH
Supplemental Safety and Health
MSDS DATED 5-16-83.

=====
===== Physical/Chemical Properties =====

HCC:F2
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:=71.1C, 160.F
Vapor Pres:75
Vapor Density:3.04
Spec Gravity:0.884
Evaporation Rate & Reference:4.2,BUAC=1
Solubility in Water:7.4%
Appearance and Odor:CLEAR VOLATILE LIQUID,CHARACTERISTIC FRUITY ODOR.
Percent Volatiles by Volume:>99

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING MATERIAL CAN CAUSE VIGOROUS REACTION.
Hazardous Decomposition Products:CO*2,CO.

=====
===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION.OBSERVE ALL FEDERAL,STATE & LOCAL
LAWS CONCERNING HEALTH & ENVIRONMENT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United S

tates of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.