

VAN WATER & ROGERS -- ETHYL ACETATE,ETHYL ETHANOATE -- 6810-00-062-6954

=====
Product Identification
=====

Product ID:ETHYL ACETATE,ETHYL ETHANOATE

MSDS Date:01/01/1987

FSC:6810

NIIN:00-062-6954

MSDS Number: BCWVB

=== Responsible Party ===

Company Name:VAN WATER & ROGERS

Address:1575 MARLBOROUGH DR

City:RIVERSIDE

State:CA

ZIP:92507-2029

Country:US

Emergency Phone Num:NONE

Preparer's Name:NOT PROV

IDED

CAGE:09N91

=== Contractor Identification ===

Company Name:VAN WATER & ROGERS INC.,SUB OF UNIVAR

Address:6100 CARILLON POINT

Box:5932

City:KIRKLAND

State:WA

ZIP:98033

Country:US

Phone:206-889-3400

CAGE:09N91

Company Name:VAN WATERS AND ROGERS

Address:2256 JUNCTION AVE

City:SAN JOSE

State:CA

ZIP:95131

Country:US

Phone:408-435-8700/800-424-9300(CHEMTREC)

CAGE:0AN91

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:

AH5425000
Fraction by Wt: 86.5%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 13.5%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

=====
Hazards Identification
=====

Effects of Overexposure:IRR EYES,NOSE,THROAT;NARCOSIS,DERMATITIS

=====
First Aid Measures
=====

First Aid:SKIN:WASH W.SOAP & H*2O EYES:FLUSH W
. H*2O. INGESTED:GIVE 2
GLASSES H*2O; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO
FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE
CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHINGBY MOUTH.

=====
Fire Fighting Measures
=====

Flash Point:=-2.6C, 27.F
Lower Limits:2.5
Upper Limits:11.5
Extinguishing Media:WATER SPRAY,DRY CHEMICAL,CO*2
Fire Fighting Procedures:WEAR CHEM PROT. SUIT WITH SCBA. COOL CONTRS
WITH H*2O.
Unusual
Fire/Explosion Hazard:FLASHBACK ALONG VAPOR TRAIL MAY OCCUR;
VAP MAY EXPL. IF IGNITED IN AN ENCLOSED AREA.AVOID WTR ACC.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGN.SOURCES.WEAR PROTECT.EQUIPM.RUBBR
BOOT,RUBBR GLOVS,RUBBR APRON,SFTY GLASSES&SCBA IN PRESS.DEMAND
MODE-SM SPILL:MOP UP&PLACE IN DOT APPVD WST CONT;LG SPILL:DIKE
W.ABS.MTL&PUMP IN DOT APPVD W ST CONT.KEEP OUT OF SEWERS,WTRWAYS.

=====
Handlin
=====

g and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT,SHOCK,FRICTION. KEEP CONTAINERS CLOSED.

Other Precautions:WASH THOROUGHLY AFTER HANDLING.DO NOT GET IN EYES,SKIN OR CLOTH.OBEY HAZ WARNING ON CONT.EVEN WHEN EMPTY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXCED TLV,NIOSH/MSHA APPR SELF-CNTND BRTHG APP (POS PR MODE)

Ventilation:PROVIDE MEC HAN(GEN/LOCAL EXHAUST)VENT TO MAINTN