

GC ELECTRONICS CO,SUB OF HOUSEHOLD INTERNATIONAL C -- CORONA DOPE --
5970-00-063-0685

===== Product Identification =====

Product ID:CORONA DOPE

MSDS Date:03/07/1989

FSC:5970

NIIN:00-063-0685

MSDS Number: BCWVX

=== Responsible Party ===

Company Name:GC ELECTRONICS CO,SUB OF HOUSEHOLD INTERNATIONAL C

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Info Phone Num:815-

968-9661

Emergency Phone Num:815-968-9661

Preparer's Name:VERE HAGEMAN

CAGE:EO032

=== Contractor Identification ===

Company Name:ELECTRONIC TOOL COMPANY, INC.

Address:241 BLEAKLEY AVE

Box:158

City:BUCHANAN

State:NY

ZIP:10511

Country:US

Phone:914-769-1000

CAGE:51380

Company Name:GC ELECTRONICS CO,SUB OF HOUSEHOLD INTERNATIONAL C

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Phone:815-968-9661

CAGE:EO032

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE EFFECTS:EYE,SKIN,RESPIRATORY AND
GASTROINTESTINAL IRRITATION,CENTRAL NERVOUS SYSTEM EFFECTS. CHRONIC
EFFECTS:NONE SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:NOT A CARCINOGEN.
Effects of Overexposure:EYES:IRRITATION,BLURRED VISION. SKIN:
IRRITATION,DERMATITIS. IN
HALATION:DIZZINESS,FATIGUE,NAUSEA,NASAL
AND RESPIRATORY IRRITATION. INGESTION:NAUSEA,DIARRHEA.
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH A HISTORY OF SKIN
OR RESPIRATORY DISEASES MAY BE MORE ADVERSELY AFFECTED.

=====
First Aid Measures
=====

First Aid:FIRST AID-EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.SEE
DOCTOR. SKIN:REMOVE CONTAMINATED CLOTHING AND SHOES. WASH WITH SOAP
AND WATER.SEE DOCTOR. INHALATION: REMOVE VICTIM TO
FRESH AIR.GIVE
OXYG EN/CPR IF NEEDED.SEE DOCTOR. INGESTION:DO NOT INDUCE VOMIT,SEE
DOCTOR.

=====
Fire Fighting Measures
=====

Flash Point Method:OC
Flash Point:41.0F,5.0C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/
Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. VENTILATE AREA.
USE NON-SPARKING TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT. STOP
LEAK.ABSORB IN INERT ABSORBENT AND PLACE INTO APPROPRIATE DISPOSAL
CONTAINER AND SEAL.

=====
Handling and Storage
=====

Handling and Storage Precaut

ions:STORE IN COOL,DRY,WELL VENTILATED
PLACE,AWAY FROM HEAT,IGNITION SOURCES AND INCOMPATIBLE
MATERIALS.KEEP CONTAINERS CLOSED WHEN NOT IN USE.
Other Precautions:AVOID BREATHING VAPORS, AND EYE AND SKIN CONTACT. USE
ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA RESPIRATOR WITH ORGANIC VAPOR
CARTRIDGE APPROPRIATE FOR EXPOSURE OF CONCERN OR SCBA IF TLV IS
EXCEEDED.

V

entilation:SUFFICIENT MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS.

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR
PROLONGED SKIN CONTACT. EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:AVOID CONTACT WITH EYES & SKIN.DO NOT BREATHE
VAPORS.WASH THOROUGHLY AFTER HANDLING.LAUNDER CONTAMINATED
CLOTHING.

Supplemental Safety and Health

THIS I

S A NEW FORMULATION.FOR OLD FORMULATION,SEE PNI A,SAME NSN. THESE
PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING. USE AT ELEVATED
TEMPERATURES MAY REQUIRE ADDED PRECAUTIONS.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:160F,71C

Vapor Pres:31

Vapor Density:1

Spec Gravity:0.89

Evaporation Rate & Reference:1 (BUTYL ACETATE = 1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK LIQUID.

Percent Volatiles by Volume:80

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.