

WACKER SILICONE CORP -- SSILICONE FLUID SWS-101 -- 9150-00-066-2382

=====  
Product Identification  
=====

Product ID:SSILICONE FLUID SWS-101  
MSDS Date:05/07/1990  
FSC:9150  
NIIN:00-066-2382  
MSDS Number: BCXBQ  
=== Responsible Party ===  
Company Name:WACKER SILICONE CORP  
Address:3301 SUTTON RD  
City:ADRIAN  
State:MI  
ZIP:49221  
Country:US  
Info Phone Num:517-263-5711  
Emergency Phone Num:517-263-5711  
CAGE:4M768

=== Contractor Identification ===  
Company Name:WACKER SILICONE CORP  
Address:3301 SUTTON RD  
City:ADRIAN  
State:MI  
ZIP:49221  
Country:US  
Phone:517-263-5711  
CAGE:4M768

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POLYDIMETHYLSILOXANE  
CAS:9016-00-6  
RTECS #:TQ2690000  
Fraction by Wt: 100.0%  
Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:LD 50 FEMALE RAT>34,600 MG/KG  
Routes of Entry: Inhalatio

n:UNKNOWN Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:N/RTE:PER MSDS MATERIAL IS NONE  
TOXIC.MAY CAUSE TEMPORARY EYE IRRITATION.  
Explanation of Carcinogenicity:DATA PER MGF MSDS.  
Effects of Overexposure:MAY CAUSE TEMPORARY EYE IRRITATION.  
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE  
WORSEN.

=====  
===== First Aid Measures =====

First Aid:EYES AND SKIN:FLUSH WITH LARGE  
AMOUNT OF WATER FOR ABOUT  
15-20 MINUTES;SEEK MEDICAL ATTENTION IMMEDIATELY.INHALATION:REMOVE  
TO FRESH AIR;CALL A PHYSICIAN.INGESTION:SEEK MEDICAL ATTENTION  
IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:>460F,>238C  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMIC  
AL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:NONE EXPECTED

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP GROSS QTY. COVER SUFACE WITH A DRY  
POWDER,BRUSH BACK & FORTH,SWEEP UP.REMOVE REMAINING DUST OR POWDER  
WITH A SAWDUST-TYPE SWEEPING COMPOUND.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL V  
ENTILATED  
AREA.KEEP CONTAINER CLOSED WHEN NOT IN USE.  
Other Precautions:CLEAN UP SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED IF USED WITH ADEQUATE  
VENTILATION.  
Ventilation:NORMAL ROOM VENTILATION.  
Protective Gloves:AS REQUIRED  
Eye Protection:SAFETY GLASSES/GOGGLES  
Other Protective Equipment:APRON, EYE-WASH FACILITIES  
Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO

NOT BREATHE

VAPORS/MIST/DUST.WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

CLEAN UP SPILLS COMPLETELY AS RESIDUE IS SLIPPERY.VISCOSITY GRADE IS  
1.0 CST.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: