

AMERON INDUSTRIAL COATING DIVISION -- 794-420 -- 8010-00-068-8783

===== Product Identification =====

Product ID:794-420

MSDS Date:01/01/1985

FSC:8010

NIIN:00-068-8783

MSDS Number: BCXFL

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATING DIVISION

Emergency Phone Num:316-733-1361

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201

N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 3.1%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 20.4%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000

LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 9.7%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 17.8%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:LEAD (SARA III)
CAS:7439-92-1
RTECS #:OF7525000
Fraction by Wt: 1.1%
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH
TLV:0.15 MG/M3;DUST 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

Effects of Overexposure:INHALE:ANESTHETIC,IRRITATION OF RESPIRATORY
TRACT,ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY

=====
===== First Aid Measures =====

First Aid:INCASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER
WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH
AIR.CALL A PHYSICIAN IF SYMPTOM

S PERSIST

===== Fire Fighting Measures =====

Flash Point:45F,7C TCC

Lower Limits:1.0

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL;POLYMER
FOAM-LARGE FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD UP

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL
SOURCES OF IGNITION(FLAMES,HOT
SURFACES,AND ELECTRICAL,STATIC,OR FRICTIONAL SPARKS)AVOID
BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA
CLASS ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOU
LD BE GROUNDED

WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME
CUT,BRAZE OR WELD COATED MATERIAL WITHOUT VENTILATION

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY&WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CON
TACT TO

CONTAMINATED CLOTHING

Supplemental Safety and Health

BP79-153C EFFTS. OF

OVEREXPOSURE-HEADACHE,DIZZINESS ETC. OR COMA.PRIMARY IRRITATION FOR
SKIN OR EYE CONTACT

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:174-308F

Evaporation Rate & Reference: