

PRATT & LAMBERT-WICHITA DIV. -- 745-406 -- 8010-00-081-0809

===== Product Identification =====

Product ID:745-406

MSDS Date:01/01/1985

FSC:8010

NIIN:00-081-0809

MSDS Number: BCXVM

=== Responsible Party ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Emergency Phone Num:316-733-1361

CAGE:KO010

=== Contractor Identification ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Box:2153

CAGE:KO010

Company Name

:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 5.35%

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 45.0%

OSHA PEL:100 PPM

=====

===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC & IRRITATION TO  
AIRWAY;IRRITATION-SKIN/EYE.HEADACHE,DIZZY,COMA.

===== First Aid Measures =====

First Aid:FLUSH SKIN/EYES WITH PLENTY OF WATER. REMOVE CONTAMINATED  
CLOTHING. INHAL:REMOVE TO FRESH AIR. CALL MD.IF NEEDED.

===== Fire Fighting Measures =====

Flash Point:104 F, 40 C, TCC

Lower Limits:1.1

Extinguishing Media:C

ARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE  
FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE  
FOR FIREMEN.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESSURE BUILD-UP.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF  
IGNITION(FLAME,SPARKS...). AVOID BREATHING VAPORS. VENTILATE AREA.  
REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE  
AMTS.IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS  
ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT INGEST.GROUND CONTAINERS WHEN POURING.AVOID  
FREE FALL OF A FEW INCHES. DO NOT FLAME CUT,BRAZE,OR WELD COATED  
MATERIAL W/O VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Pr

Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER  
FILTER OR HOOD  
Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING  
Protective Gloves:ALOT OF CONTACT  
Eye Protection:USE EYEWEAR OF SPLASHING  
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING.  
Supplemental Safety and Health  
BOILING RANGE 155-189C.

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:311-373 F  
Evaporation Rate & Refer  
ence:< ETHER  
Appearance and Odor:DARK GREEN PAINT.  
Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW LOCAL,STATE AND FED.REGULATIONS.  
INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED  
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.