View NSN Online: https://aerobasegroup.kr/nsn/8010-00-082-2440

CRAWFORD LABORATORIES, INC. -- POLYAMID, COMP II UO-082 -- 8010-00-082-2440

Product ID:POLYAMID, COMP II UO-082

MSDS Date:10/20/1987

FSC:8010

NIIN:00-082-2440

Kit Part:Y

MSDS Number: BCXYP === Responsible Party ===

Company Name: CRAWFORD LABORATORIES, INC.

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL ZIP:60609 Country:US

Info Phone Num:312-376-7132

Emer

gency Phone Num:312-433-1307

CAGE:DO165

=== Contractor Identification ===

Company Name: CRAWFORD LABORATIES, INC

Address:4165 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL ZIP:60609

Phone:800-424-9300 CHEMTREC

CAGE:DO165

Company Name: CRAWFORD LABORATORIES, INC

Address:4165 SOUTH EMERALD AVENUE

Box:City:CHICAGO

State:IL ZIP:60609 Country:US

Phone:312-376-7132

CAGE:5V430

======= Composition/Information on Ingredients ========

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III

) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 20-50% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS
Ingred Name:ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 20-50% OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:TOXICITY MAY CAUSE HEADACHE,
DIZZINESS, NAUSEA, AND LOSS OF CONSCIOUSNESS. EYE IRRITATION, IRRITATED MUCOUS MEMBRANES, VOMITING DUE TO INGESTION, DEFATTING AND DRYING OF THE SKIN. Effects of Overexposure:OVEREXPOSURE MAY PRODUCE VARIOUS EFFECTS-ACUTE TOXICITY, EYE IRRITATON, IRRITATED MUCOUS MEMBRANES, VOMITING, SKIN IRRITATION & DERMATITIS.
======================================
First Aid:DO NOT INDUCE VOMITING, EYE CONTACT-FLUSH EYES WITH WATER FOR 15 MINUTES, INHALATIO N-REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF NECESSARY. KEEP VICTIM QUIET. SKIN CONTACT-FLUSH WITH WATER-REMOVE CONTAMINATED CLOTHING, WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IMMEDIATELY.
======================================
Flash Point Method:SCC Flash Point:22F/-5.56C Lower Limits:2. Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL

Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS
COOL AND TO KEEP FLAMMABLE STRU

CTURES WET. DO NOT ENTER FIRE AREA W/O PROPER PROTECTION. Unusual Fire/Explosion Hazard:SEALED CONTAINERS MAY EXPLODE IF OVERHEATED. WATER PRESSURE MAY SPREAD A FLAMMABLE LIQUID FIRE.
======== Accidental Release Measures =========
Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITH AN ABSORBENT AND PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTLY FOR PROPER DISPOSAL.
======================================
Handling and Storage Precautions:TREAT AS A HAZARDOUS-FLAMMABLE MATERIAL. KNOW APPLICABLE DOT REGULATIONS BEFORE ATTEMPTING TO TRANSPORT THIS MATERIAL.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:MUST PROVIDE ADEQUATE VENTILATION TO KEEP VAPOR CONCENTRATIONS BELOW ESTABLISHED TLV LIMIT. IN MORE CONFINED AREAS A NIOSH-MSHA APPROVED RESPIRATOR EQUIPPED WITH ORGANIC VAPOR CART RIDGE SHOULD BE WORN
Ventilation:MUST PROVIDE ADEQUATE VENTILATION Protective Gloves:RUBBER GLOVES
Eye Protection:APPROVED SAFETY GOGGLES AND FACESHIELD Other Protective Equipment:HAVE EYE BATH AVAILABLE Supplemental Safety and Health
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:175-180F Vapor Density:>AIR Evaporation Rate & Description and Odor:CLEAR LIQUID Percent Volatiles by Volume:78.6
======================================

bility	/ and	Reactivity	/ Data	
--------	-------	------------	--------	--

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS AND STRONG ALKALIES.
Stability Condition to Avoid:AVOID HEAT, SPARKS, OPEN FLAMES AND
INCOMPATIBILITIES ABOVE HIGH TEMPERATURE, STRONG OXIDIZING
CONDITIONS.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION FOR PRODUCTS LIKE THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER TOXIC GASES.

	Disposal Considerations	
--	-------------------------	--

Was

te Disposal Methods:DISPOSE IN ACCORDANCE WITH CURRENT LOCAL, STATE AND FEDERAL REGULATION. CONTACT AN APPROVED DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.