View NSN Online: https://aerobasegroup.com/nsn/8010-00-082-2450

ENTERPRISE CHEMICAL COATINGS CO-DIV INSILCO CORP -- 990T003 MIL P 23377D COMPONENT B -- 8010-00-082-2450

Product ID:990T003 MIL P 23377D COMPONENT B MSDS Date:06/18/1986 FSC:8010 NIIN:00-082-2450 Kit Part:Y **MSDS Number: BCXYZ** === Responsible Party === Company Name: ENTERPRISE CHEMICAL COATINGS CO-DIV INSILCO CORP Address:2841 S ASHLAND AVE City:CHICAGO State:IL Ζ IP:60608-5322 Country:US Info Phone Num:312-541-9000 Emergency Phone Num:312-541-9000 CAGE:60035 === Contractor Identification === Company Name: ENTERPRISE CHEMICAL COATING CO DIV OF INSILCO CORP Address:2841 S ASHLAND Box:City:CHICAGO State:IL ZIP:60608-5322 Country:US CAGE:60035 Ingred Name: TOLUENE (IARC CARC- GROUP 3) *97-2* CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 15% Other REC Limits:375 MG/CUM OSHA PEL:100 PPM

ACGIH TLV:100 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL CAS:78-83-1 RTECS #:NP9625000 Fraction by Wt: 65% Other REC Limits:50 PPM OSHA PEL:300 MG/CUM ACGIH TLV:152 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN: PROL ONGED/REPEATED CONTACT MAY CAUSE INJURY, SENSITIZATION/OTHER ALLERGIC RESPONSES. Explanation of Carcinogenicity:NONE Effects of Overexposure:HEADACHE, NAUSEA

First Aid:INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. EYES: FLUSH IMMEDIATELY W/WATER. SKIN: WASH W/SOAP & WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:TCC Fla sh Point:40F Lower Limits:1.3 Upper Limits:12 Extinguishing Media:ANY CLASS B FIRE EXTINGUISHER Fire Fighting Procedures:USE FULL PROTECTIVE EQUIPMENT W/SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & OPEN FLAME.

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID VAPORS. VENTILATE AREA. CONTAIN & REMOVE W/INERT ABSORBENT & NONSPARKING TOOLS. SCRUB AREA W/5% ACETIC ACID/DETERGENT.

Handling and Storage Precautions: KEEP AWAY FROM HEAT/SPARKS/OPEN FLAME. STORE IN TIGHTLY CLOSED CONTAINERS. WHEN TRANSPORTING, DON'T EXCEED 120F.

Other Precautions: USE RESPIRATOR DUDRING SPRAYING.

Respiratory Protection:VAPOR TYPE OSHA APPROVED RESPIRATOR. Ventilation:LOCAL EXHAUST: IF HEATED/SPRAYED. MECHANICAL (GENERAL): GOOD GENERAL VENTILATION Protective Gloves:CHEMICAL RESISTANT POLYETHYLENE/RUBBER Eye Protection:SAFETY GLASSES W/SIDE SHIELDS Other Protective Equipment:SAFETY SHOWER, EYE BATH, CLEAN LONG LEG,

LONG-SLEEVE WORK CLOTHING. Work Hygienic Practices:WASH AFTER HANDLING & BEFORE EATING/SMOKING. Supplemental Safety and Health

HCC:F3 Boiling Pt:B.P. Text:180F Vapor Pres:70 Vapor Density:2.5 Spec Gravity :0.827 Evaporation Rate & amp; Reference:(BUTYL ACETATE=1): 5.7 Solubility in Water: