View NSN Online: https://aerobasegroup.kr/nsn/1630-00-106-6794

GOODYEAR AEROSPACE CORP/AKRON, OH 44315-0001 -- INSULATOR, #9536207

1630-00-106-6794

============= Product Identification ==================

Product ID: INSULATOR, #9536207

MSDS Date:01/01/1987

FSC:1630

NIIN:00-106-6794

MSDS Number: BCYWM === Responsible Party ===

Company Name: GOODYEAR AEROSPACE CORP/AKRON, OH 44315-0001

Emergency Phone Num:(216) 796-2121

CAGE:EO533

=== Contractor Identification ===

Company Name:GOO

DYEAR AEROSPACE CORPORATION

Address:1210 MASSILLON ROAD

City:AKRON State:OH ZIP:44315

Phone: (216) 796-2121

CAGE:EO533

Company Name: LORAL CORP DEFENSE SYSTEMS DIV-AKRON

Address:1210 MASSILLON RD

Box:City:AKRON

State:OH

ZIP:44315-0001 Country:US

Phone:216-796-2800

CAGE:25500

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS (CHRYSOTILE) 65-70%

RTECS #:GC2625000 Fraction by Wt: 70% ACGIH TLV:2.0 FB/CC

Ingred Name: PHENOL-FORMALDEHYDE RESIN 26-35%

Fraction b

y Wt: 35%
========== Hazards Identification ============
Effects of Overexposure:CHRONIC OVEREXPOSURE TO AIRBORNE CONCENTRATIONS OF ASBESTOS MAY LEAD TO ASBESTOSIS & MESOTHELIOMA
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ADVICE. SKIN: WASH WITH SOAP & WATER. EYE: FLOOD WITH WATER. IF IRRITATION OCCURS, SEE A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN. CHANGE CLOTHING, IF
NECESSARY/AVOID DUSTS PARTICLES IN OTHER AREAS
============= Fire Fighting Measures ===============
Flash Point:NONE Fire Fighting Procedures:COMBUSTION PRODUCTS OF THIS MATERIAL MAY BE TOXIC. USE SCBA.
======== Accidental Release Measures =========
Spill Release Procedures:VACUUM OR WET CLEAN IF DUST IS INVOLVED. VACUUM SYSTEM SHOULD BE EQUIPPED WITH AN OUET HEPA FILTER TO PREVENT REINTRODUCING ASBESTOS FIBERS TO THE ATMOSPHER
======================================
Handling and Storage Precautions:HANDLE TO MINIMIZE FORMATION OR RETENTION OF DUST.
===== Exposure Controls/Personal Protection =======
Respiratory Protection:IF >TLV, A NIOSH/MSHA APPROVED RESPIRATOR FOR ASBESTOS. Ventilation:LOCAL EXHAUST VENTILATION IS RECOMMENDED Eye Protection:SAFETY GOGGLES/FACE SHIEL Supplemental Safety and Health MSDS DATE: 4/85
========== Physical/Chemical Properties ========

======

HCC:T7 Boiling Pt:B.P. Text:NONE Solubility in Water:0 Appearance and Odor: DARK BROWN SOLID Percent Volatiles by Volume:0

	Stability and Reactivity Data	
Stability Indicator/Mate	rials to Avoid:YES	
	Disposal Considerations	

Waste Disposal Methods: DUST SHOULD BE HANDLED AS HAZARDOUS AIR POLLUTANT IN ACCORDANCE W/40 CFR 61 SUBPART M PERTAINING TO ASBESTOS, USE LANDFILLS FOR ASBESTOS DISPOSAL, SCRAP PA RTS ARE NOT

FRIABLE AND ARE NOT RESTRICTED UN DER AIR POLLUTION REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume r esponsibility for the suitability of this information to their

particular situation.