

DEFT CHEMICAL COATINGS -- 03-BL-50 BASE BLUE 15450,POLYURETHANE ENAME --
8010-00-130-7579

===== Product Identification =====

Product ID:03-BL-50 BASE BLUE 15450,POLYURETHANE ENAME

MSDS Date:01/01/1985

FSC:8010

NIIN:00-130-7579

Kit Part:Y

MSDS Number: BCZZC

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Emer

gency Phone Num:949-474-0400

CAGE:EO418

=== Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qt

y:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)
CAS:111-15-9
RTECS #:KK8225000
Fraction by Wt: 20.0%
OSHA PEL:S,100 PPM
ACGIH TLV:S, 5 PPM; 9192

Ingred Name:ETHYL ACETATE (CAS #141-78-6)
RTECS #:AH4250000
Fraction by Wt: 5.0%
ACGIH TLV:400 PPM

Ingred Name:DIBUTYL TIN DILAURATE (AS TIN)
CAS:77-58-7
RTECS #:WH7000000
Fraction by Wt: 0.01%
OSHA PEL:S, 0.1 MG/M3
ACGIH TLV:S, 0.1 MG/M3; 8990

Ingred Name:DISPERSING AGENT-ALSO SEE SUPPLEMENTAL DATA FOR
OTHER HAZ
INGRED;ENTS.
Fraction by Wt: 0.5%

=====
===== Hazards Identification =====

Effects of Overexposure:SKIN/EYES:IRRITATION;INH:IRRIT OF RESP
TRACT/ACUTE NERVOUSSYSTEM DEPRESSION;HEADACHE,DIZZINESS,ETC.

=====
===== First Aid Measures =====

First Aid:EYES:IMMED FLUSH W/LG VOLUME OF WATER FOR AT LEAST 15 MIN.GET
MED ATTN;SKIN:WASH AFFECTED AREA W/WATER.REMOVE CONTAMINATED
CLOTHING.GET MED ATTN IF IRRIT OCCURS;IN
H:REMOVE FROM
EXPOSURE.RESTORE BREATH ING BY CPR,KEEP WARM & QUIET.GET MED ATTN.

=====
===== Fire Fighting Measures =====

Flash Point:20F(-6.6C)-TCC
Lower Limits:UNK
Extinguishing Media:CARBON DIOXIDE,FOAM OR DRY CHEM.(CLASS B FIRE
EXTINGUISHER)
Fire Fighting Procedures:SELF-CNTND BRTHG APP;USE H*2O SPRAY TO COOL
FIRE EXPSD CNTNR
Unusual Fire/Explosion Hazard:CLOSD CONTNRS MAY EXPLODE IN HEAT OF
FIRE;SPILL/RUNOFF MAYCAUSE POLLUTION,FIRE,&/OR EXPLOSIO

N HAZARD

===== Accidental Release Measures =====

Spill Release Procedures:ELIM IGN SOURCES.VENTILATE AREA.USE PROTECTV EQUIP.STOP LEAK W/O RISK.SM SPILL:CONTAIN/REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.PLACE IN COVERD CINTNRS;LG SPILL:KIKE AREA & PUMP LIQ TO SALVAGE TA NK.ABSORB REMAINING LIQ & SHOVEL UP INTOCONTAINR.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY WELL VEN TILATED,LOW

FIRE RISK AREA.KEEP CLOSURE TIGHT & CNTNR UPRIGHT.STORE AWAY FM IGN/HEAT SOURCES.PROTECT FM PHYSICAL DAMAGE.

Other Precautions:PREVENT PROLONGD/REPEATD BREATHING OF VAP OR SPRAY MIST.CAN CAUSE ALLERGIC REACTION.FOLLOW SPECIAL PRECAUTIONS TO APPLY ON HOT SURFACES.IF WATER IS USED FOR FIRE,FOG NOZZLES ARE PREFERABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESP FOR PAINT,LAQUER,ENAMEL MISTS,ORGA NIC VAPORS,ETC

Ventilation:ADEQUATE USING EXHAUST FAN OR IAW 29CFR PART 1910.94

Protective Gloves:NEOPRENE/RUBBER

Eye Protection:SAFETY GLASSES W/SIDESHLD

Other Protective Equipment:CLEAN,LONG SLEEVE/LONG LEG PROTECTIVE CLOTHING.

Supplemental Safety and Health

MSDS FM MFR DATE:12/08/80;TWO PART RESIN MODIFIED POLYURETHANE COATING;THIS DATA DESCRIBES BASE;SEE P/N IND "B" FOR CATALYST;ALSO CONTAINS:1.0

Spec Gravity:1.3301

Evaporation Rate & Reference: