

TEXACO,INC -- 01543 ROCK DRILL LUBE 320 -- 9150-00-142-9556

===== Product Identification =====

Product ID:01543 ROCK DRILL LUBE 320

MSDS Date:01/01/1987

FSC:9150

NIIN:00-142-9556

MSDS Number: BDBWK

=== Responsible Party ===

Company Name:TEXACO,INC

Emergency Phone Num:914-831-3400,X-204

CAGE:KO140

=== Contractor Identification ===

Company Name:CONVOY OIL CORP

Address:1410 N FRONT STREET

Box:29366

City:PHILADELPHIA

State:PA

ZIP:19125

Country:US

Phone:215-739-5281

CAGE:6A438

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Phone:914-831-3400

CAGE:7B131

Company Name:TEXACO,INC

Box:509

City:BEACON

State:NY

ZIP:12508

Country:US

Phone:914-831-3400,EXT 204

CAGE:KO140

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT-DEWAXED HEAVY PARAFFINIC PETROLEUM

DISTILLATES(CAS#64742-65-0)(80-95%)

CAS:64742-65-0

RTECS #:PY8038500

Fr

action by Wt: 88%
ACGIH TLV:5MG/CUM

=====
Hazards Identification
=====

Effects of Overexposure:EYES:MINIMAL IRRITNT.SKIN:SLIGHT IRRITNT,
POSSIBLE REDNESS,EDEMA,DEGATS. RESPIR TRACT:MINIMAL IRRITNT

=====
First Aid Measures
=====

First Aid:EYES:AS WITH FOREIGN MATL,SHOULD EYE CONTACT OCCUR,FLUSH EYES
WITH PLENTY OF WATER.SKIN:WASH EXPOSED AREAS WITH SOAP & WATER.
INGEST/INHALE:NONE CONSIDERED NECESSARY.

=====
Fire Fighting Measures
=====

Flash Point:380F/193C C0C
Lower Limits:UNK
Upper Limits:UNK
Extinguishing Media:CO2, FOAM, DRY CHEM & H2O FOG.
Fire Fighting Procedures:USE WATER SPRAY TO COOL CONT, KNOCK-DOWN
VAPORS. WEAR SCBA.
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

=====
Accidental Release Measures
=====

Spill Release Procedures:CONTAIN SPILL IF POSSIBLE.WIPE UP OR ABSORB ON
SUITABLE MATERIAL AND SHOVEL UP.

=====
Handling and Storage
=====

Handling and Storage Precautions:MINIMUM FEASIBLE HANDLING TEMPS SHOULD
BE MAINTAINED;PROLONGED EXPOSURE TO HIGH TEMPS AND WATER
CONTAMINATION SHOULD BE AVOIDED.
Other Precautions:EXPOSED EMPLOYEES SHOULD PRACTICE REASONABLE PERSONAL
HYGIENE;THIS INCLUDES WASHING THOROUGHLY SEVERAL TIMES A DAY;AND
REMOVING AND LAUNDERING CONTAMINATED CLOTHING.

=====
Exposure Controls/Personal Protection
=====

=

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/
ADEQUATE VENT.
Ventilation:NORMAL
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES/FACE SHIELD
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.
Supplemental Safety and Health
MSDS DATED 11-18-85. **ON 10SEP92 AFTER A TECH SUPP REQUEST, CONVOY OIL
WAS CONTACTED AND INDICATED THAT THEY HAD SUPPLIED TEXACO OIL ON
CONTRACT DLA600-81-C-1377.**

=====
===== Physical/Chemical Properties
=====

HCC:V6
Boiling Pt:B.P. Text:NOT DETERM.
Vapor Pres:UNK
Vapor Density:UNK
Spec Gravity:0.9371
Solubility in Water:NEGLIGIBLE
Appearance and Odor:TYPICAL LUBRICATING OIL-LIQUID,SLIGHTLY ACRID ODOR
Percent Volatiles by Volume:UNK

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CO,CO2,ALDEHYDES,KETONES,COMBUS PROD.
OF NIT
ROGEN & SULFUR.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DOES NOT MEET CRITERIA FOR HAZARDOUS WASTE IF IN
ORIGINAL FORM.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any p

erson utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.