

MILITARY SPECIFICATIONS PROMULGATED BY MILITARY -- N-1030 ADHESIVE -- 8040-00-142-9913

===== Product Identification =====

Product ID:N-1030 ADHESIVE

MSDS Date:01/01/1985

FSC:8040

NIIN:00-142-9913

MSDS Number: BDBXP

=== Responsible Party ===

Company Name:MILITARY SPECIFICATIONS PROMULGATED BY MILITARY

Address:DEPTS/AGENCIES UNDER AUTH OF DEFENSE STD

Box:MANUAL

City:4120 3-M

Country:US

Info Phone N

um:800-848-4847 DSN 695-5168

Emergency Phone Num:804-279-4371 DSN 695-4371

CAGE:81349

=== Contractor Identification ===

Company Name:MILITARY SPECIFICATIONS PROMULGATED BY MILITARY

Address:DEPTS/AGENCIES UNDER AUTH OF DEF STD

Box:MANUAL

City:4120 3-M

Phone:804-279-4371 DSN 695-4371

CAGE:81349

===== Composition/Information on Ingredients =====

Ingred Name:CATALYST

Fraction by Wt: 2%

Ingred Name:VEHICLE

Fraction by Wt: 17%

Ingred Name:SOLVENTS

Fraction by Wt: 72%

Ingred Name

:ADDITIVES

Fraction by Wt: 9%

=====
Hazards Identification
=====

Effects of Overexposure:NARCOSSIS,STUPOR, DROWSINESS

=====
First Aid Measures
=====

First Aid:FRESH AIR AND/OR OXYGEN.OBTAIN MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:20 F TOC -7C

Lower Limits:1.2

Upper Limits:7.0

Extinguishing Media:CO*2,POWDER CHEMICALS, TRICHLOROETHANE

Fire Fighting Procedures:S

ELF-CONTAINED BREATHING APPARATUS NIOSH
APPROVED.

Unusual Fire/Explosion Hazard:AVOID CONTACT WITH OXIDIZERS,OPEN
FLAME,SPARKS,HOT SURFACES.

=====
Accidental Release Measures
=====

Spill Release Procedures:APPLY DRI-RITE OR SPEED-DRY ABSORBENT MATEIALS
TO SOAK UP LIQUID

=====
Handling and Storage
=====

Handling and Storage Precautions:REASONABLE CAUTION TO AVOID CONTACT
WITH SKIN.STORE IN FLAMMABLE STORAGE AREA AT
60-90 F.

Other Precautions:KEEP OUT OF DIRECT SUNLIGHT AND IN SEALED CONTAINERS

=====
Exposure Controls/Personal Protection
=====

Ventilation:PREVENT VAPOR BUILD UP. MECHANICAL-CROSS VENTILATION

Protective Gloves:YES

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:202 F 95 C

Vapor Pres:100

Vapor Density:3.06

Spec Gravity:0.875

Evaporation Rate & Reference:2.9

A

Appearance and Odor: OPAQUE CREAM COLOR, MOTHBALL, RUBBERY ODOR.
Percent Volatiles by Volume: 81.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
OXIDES OF CARBON, SULFUR, NITROGEN, ZINC, MAGNESIUM, CHLORINE, FO
Stability Condition to Avoid: OXIDIZERS, OPEN FLAME, SPARKS, HOT SURFACES
Hazardous Decomposition Products: NO

===== Disposal Considerations =====

Waste Disposal Methods: SOLVENT WASTE STEEL DRUM.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.