

AMERON INDUSTRIAL COATINGS DIVISION -- 745-102 -- 8010-00-144-9791  
===== Product Identification =====

Product ID:745-102  
MSDS Date:01/01/1985  
FSC:8010

NIIN:00-144-9791  
MSDS Number: BDBZK  
=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION  
Emergency Phone Num:316-733-1361  
CAGE:09869

=== Contractor Identification ===  
Company Name:AMERON INDUSTRIAL COATINGS DIVISION  
Address:20  
1 N BERRY ST  
Box:City:BREA  
State:CA  
ZIP:92621-3904  
Country:US  
Phone:714-529-4597  
CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
Fraction by Wt: 44.0%  
OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:INHALE:ANESTHETIC,IRRITATION TO AIRWAY,& IF  
SKIN/EYE CONTACT,HEADACHE,DIZZINESS,COMA

===== First  
Aid Measures =====

First Aid:INCASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER  
WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED,,REMOVE TO FRESH  
AIR.CALL A PHYSICIAN IF SYMPTOMS PERSIST

===== Fire Fighting Measures =====

Flash Point:85F,29C TCC  
Lower Limits:1.1  
Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL;POLYMER  
FOAM-LARGE FIRE  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE  
FOR FIREME

N

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD UP

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT SURFACES,& ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions

:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE(OR COMBUSTIBLE)LIQUID

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME CUT,BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY&WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING

Supplemental Safety and Health

BP 155-189C

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:311-373F

Evaporation Rate & Reference:< ETHER

Percent Volatiles by Volume:60.0

===== Stability

and Reactivity Data =====

Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE, AND  
FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY.DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.