

VINELAND WAY SPECIALTIES, INC. -- LUB OIL, MACHINE TOOL SLIDEWAYS -- 9150-00-145-0112

=====  
Product Identification  
=====

Product ID:LUB OIL, MACHINE TOOL SLIDEWAYS  
MSDS Date:01/01/1987  
FSC:9150  
NIIN:00-145-0112  
MSDS Number: BDCCX  
=== Responsible Party ===  
Company Name:VINELAND WAY SPECIALTIES, INC.  
Emergency Phone Num:609-697-3152  
CAGE:KO264  
=== Contractor Identification ===  
Company Name:VINELAND  
WAX SPECIALTIES INC WAX PROCESSING  
Address:S RAILROAD BLVD  
Box:City:MINOTOLA  
State:NJ  
ZIP:08341  
Country:US  
Phone:609-697-3941 (OUT OF BUSINESS)  
CAGE:63400  
Company Name:VINELAND WAY SPECIALTIES, INC.  
CAGE:KO264

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM HYDROCARBON  
ACGIH TLV:5 MG/CUM (MIST)

=====  
Hazards Identification  
=====

Effects of Overexposure:EYE & SKIN IRRIT

=====  
First Aid Measures  
=====

First Aid:EYE:IMMED FLUSH W/PLENTY OF WATER FOR 15 MINUTES. GET MED  
ATTN. SKIN:WASH W/SOAP & WATER.

=====  
Fire Fighting Measures  
=====

Flash Point:400F,204  
Lower Limits:0.9  
Upper Limits:7.0  
Extinguishing Media:FOAM, WATER SPRAY(FOG),DRY CHEMICAL, CARBON  
DIOXIDE.  
Fire Fighting Procedures:USE WATER SPRAY TO KEEP FIRE-EXPOSED  
CONTAINERS COOL.  
Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

=====

Spill Release Procedures:RECOVER FREE PRODUCT W/VACUUM OR PUMP. ABSORB W/INERT MATL AND PICK UP/SHOVEL INTO SEALED DRUM. DIKE TO RETAIN LG SPILLS. KEEP OUT OF SEWERS AND WATER-COURSE

===== Handling and Storage =====

Handling and Storage Precautions:WASH SKIN THOROUGHLY AFTER HANDLING. LAUNDER SOILED WORK CLOTHS BEFORE REUSE. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FM PHYSICAL DAMAGE.

Other Precautions:NONE

=====

==== Exposure Controls/Personal Protection =====

Respiratory Protection:IF REQD BY HIGH TEMP FUMES,USE NIOSH APPROVED SCBA.

Ventilation:LOCAL REQD FOR VAPOR/MIST/FUMES

Protective Gloves:RUBBER/NEOPRENE

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:NONE

Supplemental Safety and Health

MSDS DATED 20 JAN 1987

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:560F,293C

Vapor Pres:NIL

Vapor Density:>75

Spec Gravity:0.90

Ev

aporation Rate & Reference:DARK OILY LIQUID,

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PETROLEUM ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:EXTREME HEAT OR OPEN FLAME.

Hazardous Decomposition Products:TOXIC FUMES & SMOKE, CO, SULFUR OXDES

===== Disposal Considerations =====

Waste Disposal Methods:DISP

OSE BY INCINERATION I/A/W ALL APPLICABLE  
LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.