View NSN Online: https://aerobasegroup.com/nsn/8010-00-160-5787

Product ID:266C

MSDS Date:01/01/1985

FSC:8010

NIIN:00-160-5787

MSDS Number: BDDFS === Responsible Party ===

Company Name: MINNESOTA MINING & MFG CO SALES CENTER

Address:100 ANDOVER PARK W

City:SEATTLE State:WA

ZIP:98188-2801 Country:US

Info Phone Num:612-733-5454

Emergency Phone Num:612-733-5454

С

AGE:2K194

=== Contractor Identification ===

Company Name: MINNESOTA MINING AND MFG CO SALES CENTER

Address:3245 146TH PL SE SUITE 200

Box:City:BELLEVUE

State:WA ZIP:98007 Country:US

Phone:612-733-5454

CAGE:2K194

======= Composition/Information on Ingredients ========

Ingred Name: ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000 OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3 RTECS #:EO

1400000 **OSHA PEL:100 PPM** ACGIH TLV:S, C 50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: METHYL ISOBUTYL KETONE (SARA III) CAS:108-10-1 RTECS #:SA9275000 OSHA PEL:100 PPM/75 STEL ACGIH TLV:50 PPM/75 STEL; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: ISOBUTYL ALCOHOL (SARA III) CAS:78-83-1 RTECS #:NP9625000 OSHA PEL:100 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: N-BUTYL ACETATE (SARA III) CAS:123-86-4 RTECS #:AF7350000 OS HA PEL:150 PPM/200 STEL ACGIH TLV:150 PPM/200STEL;9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Effects of Overexposure: DIZZINESS, HEADACHE, LOSS OF COORDINATION,

Effects of Overexposure:DIZZINESS, HEADACHE, LOSS OF COORDINATION, SLIGHT EUPHORIA, LIGHT-HEADED FEELING.

First Aid:INHALATION: REMOVE TO OPEN AIR, RECOVERY USUALLY RAPID. EYE OR SKIN CONTACT: FLUSH IMMEDIATELY WITH WATER. INGESTION: DO NOT INDUCE V

========== Fire Fighting Measures ===========
Flash Point:70F T.C.C. Lower Limits:1.5 Upper Limits:11 Extinguishing Media:CO2, DRY CHEMICAL, FOAM Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS RECOMMENDED Unusual Fire/Explosion Hazard:FLAMES MAY BE DIFFICULT TO SEE (BLUE FLAME). AVOID GETTING CLOSE.
======== Accidental Release Measures ==========
Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION IN VICINITY OF SPILL, VENTILATE WELL TO RELEASE VARS, CLEAN UP AS SOON AS POSSIBLE.
=========== Handling and Storage ============
Handling and Storage Precautions:DANGER-HARMFUL OR FATAL IF SWALLOWED. KEEP AWAY FROM OPEN FLAME. USE IN WELL-VENTILATED AREA. OID CONTACT WITH SKIN OR EYES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:ORGANIC VAPOR RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS Ventilation:KEE P BELOW TLV. Protective Gloves:NEOPRENE/RUBBER Eye Protection:GOGGLES Other Protective Equipment:AVOID SKIN CONTACT - MAY IRRITATE. Supplemental Safety and Health ALSO CONTAINS METHYL ETHYL KETONE, TLV-200PPM; ISOPROPYL ALCOHOL, TLV-400PPM.
========= Physical/Chemical Properties ==========
HCC:F2 Boiling Pt:B.P. Text:176-251F Vapor Pres:19 Vapor Density:3.3 Spec Gravity:0.815 Evaporation Rate & Description Rate & D

OMITING, CALL PHYSICIAN.

Percent Volatiles by Volume:99+
Stability and Reactivity Data
Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZING AGENTS Hazardous Decomposition Products:NORMAL COMBUSTION PRODUCTSCO2 AND WATER

Waste Disposal Methods:FLUSH WELL WITH WATER, FLUSH DRAIN WITH WATER TO AVOID VAPOR BACK-UP.

======= Disposal Considerations ===========

Disclaimer (provided with this inform ation by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.