

ASHLAND OIL -- TT-T-266 D -- 8010-00-160-5788

===== Product Identification =====

Product ID:TT-T-266 D
MSDS Date:01/01/1985
FSC:8010
NIIN:00-160-5788
MSDS Number: BDDGK
=== Responsible Party ===
Company Name:ASHLAND OIL
Address:1409 WINCHESTER AVE
Box:391
City:ASHLAND
State:KY
ZIP:41114
Country:US
Emergency Phone Num:606-329-3333
CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND I
NC
Address:1409 WINCHESTER AVE
Box:391
City:ASHLAND
State:KY
ZIP:41114
Country:US
Phone:800-622-6846
CAGE:81355

===== Composition/Information on Ingredients =====

Ingred Name:KETONES(TYPE NOT SPECIFIED)
Fraction by Wt: 20%
ACGIH TLV:200 PPM

Ingred Name:ALIPHATIC HYDROCARBONS
Fraction by Wt: 20%
ACGIH TLV:350 MG/CUM

Ingred Name:KETONE(TYPE NOT SPECIFIED)
Fraction by Wt: 5%
ACGIH TLV:100 PPM

Ingred Name:ALCOHOLS(TYPE NOT SPECIFIED)
Fraction by Wt: 5%
ACGIH TLV:400 PPM

Ingre

d Name:ESTER
Fraction by Wt: 20%
ACGIH TLV:150 PPM

===== Hazards Identification =====

Effects of Overexposure:EYES/SKIN:MODERATE IRRITNT.INHALE:RESPIR
IRRITNT,NAUS,ASPHX.INGEST:GI IRRITNT.VOMIT,CHEM PNEUMONITS

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH LARGE AMOUNTS WATER.SKIN:WASH EXPOSED AREA
WITH SOAP & WATER.INGEST:DO NOT INDUCE VOMIT.KEEP
WARM,QUIET.INHALED:REMOVE TO FRESH AIR.GIVE CPR/OXYG
EN IF NEED.KEEP
WARM QUIET.IF SYMPTOMS PERSIST IN ALL CASES,GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:1
Spec Gravity: