

CHEMRAY COATINGS CORPORATION -- TT-P-664 PRIMER COATING -- 8010-00-161-7275
===== Product Identification =====

Product ID:TT-P-664 PRIMER COATING
MSDS Date:01/01/1985
FSC:8010
NIIN:00-161-7275
MSDS Number: BDDMD
=== Responsible Party ===
Company Name:CHEMRAY COATINGS CORPORATION
Address:209 MICHIGAN AVE.
City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Emergency Phone Num:201-245-1111
CAGE:OBRN9

===
Contractor Identification ===
Company Name:CHEMRAY COATING CORP
Address:209 N MICHIGAN AVE
Box:City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Phone:201-245-1111
CAGE:33832
Company Name:CHEMRAY COATINGS CORP.
Address:209 N. MICHIGAN AVE.
Box:NA
City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Phone:800-924-9300
CAGE:OBRN9

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTANOL; MFR STATES THAT ALONG W/VM & P NAPHTHA & TOLUENE
COMPRISES 39.6% OF PRODUCT.
ACGIH

TLV:S,C,50 PPM

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ALKYD RESIN

Fraction by Wt: 20.8%

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: 3.95%

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

=====
ion =====
Hazards Identificat

Effects of Overexposure:INH:HDCH/DIZZ/UNCONS/COMA. EYE:PRIMARY IRRIT.
SKIN:PRIMARY IRRIT/DRYING.

=====
First Aid Measures =====

First Aid:INH:MOVE FROM EXPOSURE,RESTORE BRTHNG. KEEP WARM,CALL MD.
EYES:FLUSH W/WATER AT LEAST 15 MINS, SEE MD. SKIN:REMOVE
CONTAMINATED CLTHNG. WASH AFFECTED AREA W/SOAP & WATER. CALL MD.

=====
Fire Fighting Measures =====

Flash Point:55F,13C SCC
Lower L

imits:0.7

Upper Limits:11.2

Extinguishing Media:CO*2,DRY CHEMICAL,FOAM;WATER SPRAY MAY BE INEFFECTIVE.

Fire Fighting Procedures:WEAR SCBA. USE WATER FOG TO COOL CLSD CNTNR TO PRVNT PRESS.

Unusual Fire/Explosion Hazard:CLOSED CNTNRS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE WITH ABSORBENT MATERIAL OR FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER.

AVOID SPARKS,FIRE AND HOT

SURFACES. VENTILATE AREA. WEAR PROT EQUIP. REMOVE CONTAMINATED CLTHNG & WASH SKIN. KEEP O UT OF MUNICIPAL SEWERS & OPEN BODIES OFWATER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS, OPEN FLAME. USE W/ADEQUATE VENTILATION. AVOID TIGHTLY WHEN NOT IN USE.

Other Precautions:DO NOT TAKE INTERNALLY. FLAMMABLE! AVOID BUILDUP/BRTHNG OF VAPORS. EMPTY CNTNR MAY BE HAZARD-MAY C ONTAIN EXPLOSIVE VAPORS/DANGEROUS RESIDUE,SUBJ TO AUTO IGNITION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED

Ventilation:ADEQUATE TO MAINTAIN EXPOSURE BELOW TLV

Protective Gloves:FOR RPTD CNTCT

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:IMPERMEABLE APRON FOR RPTD CNTCT. EYE WASH/SAFETY SHOWER.

Supplemental Safety and Health

CONTAINER SIZE:5 GAL. BP:110-199C(SOLVENT). HAZ INGRED:1000972AS ADDITIVES,