

KOPPERS COMPANY, INC. -- TT-P-664C RUST INHIBITING PRIMER -- 8010-00-161-7275

=====
Product Identification
=====

Product ID:TT-P-664C RUST INHIBITING PRIMER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-161-7275

MSDS Number: BDDMJ

=== Responsible Party ===

Company Name:KOPPERS COMPANY, INC.

Address:3000 KOPPERS BLDG

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

CAGE:EO463

=== Contractor Identificati

on ===

Company Name:KOPPERS CO INC

Address:3000 KOPPERS BLDG

Box:City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

CAGE:80592

Company Name:KOPPERS COMPANY, INC.

CAGE:EO463

=====
Composition/Information on Ingredients
=====

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:AROMATIC HYDROCARBONS
ACGIH TLV:100 PPM

=====
===== Hazards Identification =====

Effects of Overexposure:EYE:IRRIT.SKIN:IRRIT,DEFATTING.
VAPORS:DROWSINESS,HEADACHE,DIZZINESS.

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN,GET MED ATTN.SKIN:WASH WITH SOAP
AND WATER. INHALATION:REMOVE TO FRESH AIR,ADMINISTER OXYGEN IF
NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point:65F/18C(TCC)
Extinguishing Media:WATER SPRAY,FOAM,DRY CHEMICAL,CO*2
Fire Fighting Procedures:SELF-CONT BREATH APP,WATER FOG TO COOL EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSUE BUILD UP.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SECURE SOURCES OF IGNITION. COVER WITH
ABSORBENT MATERIAL,SWEEP & PICKUP
WITH NON SPARKING TOOLS,PLACE IN
CLOSED CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR HEAT,SPARKS,OPEN
FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE AND UPRIGHT TO
PREVENT LEAKAGE.
Other Precautions:DO NOT USE IN TANK,PIT OR CONFINED AREAS WITHOUT
ADEQUATE VENTILATION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN

ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:LOCAL/MECHANICAL EXHAUST
Protective Gloves:RUBBER
Eye Protection:GOGGLES
Supplemental Safety and Health
CONTAINER SIZE: 5 GAL CAN

===== Physical/Chemical Properties =====

HCC:F3
Vapor Density:>1
Evaporation Rate & Reference:>1 (N-BU-AC)
Solubility in Water:SLIGHT
Appearance and Odor:RED COLOR,TYPICAL PAINT ODOR
Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.