

ALLOY RODS CORPORATION -- ATOM ARC 11018M 0.156 10LB -- 3439-00-165-4165

=====
Product Identification
=====

Product ID:ATOM ARC 11018M 0.156 10LB
MSDS Date:06/06/1986
FSC:3439
NIIN:00-165-4165
MSDS Number: BDDSW
=== Responsible Party ===
Company Name:ALLOY RODS CORPORATION
Address:WILSON AVENUE
Box:517
City:HANOVER
State:PA
ZIP:17331
Info Phone Num:717-637-8911
Emergency Phone Num:717-637-8911
CA
GE:84021

=== Contractor Identification ===
Company Name:ESAB GROUP INC
Address:801 WILSON AVENUE
Box:517
City:HANOVER
State:PA
ZIP:17331
Country:US
Phone:717-637-8911 OR 800-933-7070
CAGE:84021

=====
Composition/Information on Ingredients
=====

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
Other REC Limits:5MG/M*3
OSHA PEL:10MG/M*3
ACGIH TLV:5MG/M*3

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Other REC Limits:10MG/M*3
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDU

ST; 9293

Ingred Name:SODIUM SILICATE

CAS:6834-92-0

RTECS #:VV9275000

OSHA PEL:5MG/M*3 (RESP. DUST)

ACGIH TLV:0.1MG/M*3(RESP.DUST)

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Other REC Limits:10MG/M*3

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Other REC Limits:10MG/M*3

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9

275000

Other REC Limits:5MG/M*3 (C)

OSHA PEL:(C) 5 MG/M3 DUST

ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

Ingred Name:POTASSIUM SILICATE

CAS:1312-76-1

OSHA PEL:5MG/M*3 (RESP.DUST)

ACGIH TLV:0.1MG/M*3(RESP.DUST)

Ingred Name:CALCIUM FLUORIDE

CAS:7789-75-5

RTECS #:EW1760000

Other REC Limits:2.5MG/M*3

OSHA PEL:2.5 MG/M3 (F)

ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:POTASSIUM FELDSPAR

Other REC Limits:10MG/M*3

(NUISANCE)
OSHA PEL:NOT LISTED
ACGIH TLV:NOT LISTED

Ingred Name:ZIRCON (ZIRCONIUM IV,SILICATE)
CAS:14940-68-2
RTECS #:ZH9000000
Other REC Limits:5 MG/M*3
OSHA PEL:5 MG/M3/10 STEL (ZR)
ACGIH TLV:5 MG/M3/10 STEL (ZR)

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
Other REC Limits:0.5MG/M3
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MOLYBDENUM
CAS:7439-98-7
RTECS #:QA4680000
Other REC Limits:5MG/M*3
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:1
0 MG/M3; 9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS
OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE,THROAT.
CHRONIC:EXCESSIVE LEVELS MAY CAUSE BRONCHIAL ASTHMA,LUNG
FIBROSIS,SIDEROSIS. ARC RAYS CAN INJURY EYES & BURN SKIN. ELECTRIC
SHOCK CAN KILL.

Explanati

on of Carcinogenicity:CHROMIUM VI IS A HUMAN CARCINOGEN.
CHROMIUM III IS A SUSPECTED HUMAN CARCINOGEN. NICKEL IS A SUSPECTED
HUMAN CARCINOGEN.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY
OR ALLERGIC CONDITIONS. HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG
SMOKERS.

=====
===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE & OBTAIN PROMPT MEDICAL ATTENTION. IF
NOT

BREATHING,GIVE CPR. IF UNCONSCIOUS,GIVE OXYGEN. EMPLOY FIRE AID TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

=====
Fire Fighting Measures
=====

Flash Point:NONE

Extinguishing Media:APPROPRIATE FOR SURROUNDING FIRE.

Unusual Fire/Explosion Hazard:WELDING ARCS & SPARKS CAN IGNITE COMBUSTIBLE PRODUCTS.

=====
Accidental Release Measures
=====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE & PLACE IN A APPROPRIATE DISPOSAL CONTAINER.

=====
Handling and Storage
=====

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES. MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:

LOCAL EXHAUST

Protective Gloves:WELDER'S GLOVES

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS

Other Protective Equipment:SUBSTANTIAL DARK CLOTH,ARM PROTECTOR,APRON,HAT,SHOULDER PROTECTION.

Work Hygienic Practices:WASH AFTER HANDLING.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:N1

Appearance and Odor:WELDING ROD 0.156 INCHES DIAMETER BY 14 INCHES LONG.

=====
Stability and Reactivity Data
=====

==

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: FUMES OF METALS & METAL
OXIDES, CO, CO*2, NO*2, O*3, FLUORIDES

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IAW FEDERAL, STATE & LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.