

MOBILE PAINT MFG CO INC -- 35-EF-49;PAINT DRIER COBALT NAPHTHENATE -- 8010-00-165-4782
===== Product Identification =====

Product ID:35-EF-49;PAINT DRIER COBALT NAPHTHENATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-165-4782

MSDS Number: BDDVD

=== Responsible Party ===

Company Name:MOBILE PAINT MFG CO INC

Address:HAMILTON BLVD

Box:717

City:THEODORE

State:AL

ZIP:36582-9315

Country:US

Emergency Phone Nu

m:(205)653-0110

CAGE:88633

=== Contractor Identification ===

Company Name:MOBILE PAINT MANUFACTURING CO INC

Box:717

City:THEODORE

State:AL

ZIP:36582

Country:US

Phone:334-443-6110

CAGE:88633

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 45.0%

OSHA PEL:100 PPM

Ingred Name:COBALT NAPHTHENATE

CAS:61789-51-3

RTECS #:QK8925000

Fraction by Wt: 55.0%

===== Hazards

Identification =====

Effects of Overexposure:THIS MATERIAL CAUSES SKIN IRRITATION AFTER PROLONGED OR REPEATED CONTACT. POISONOUS IF SWALLOWED.

===== First Aid Measures =====

First Aid:WASH THOROUGHLY W/SOAP & WATER AFTER SKIN CONTACT. FOR EYES FLUSH W/WATER AT LEAST 15 MINS.

===== Fire Fighting Measures =====

Flash Point:100-110F CC

Lower Limits:0.8

Extinguishing Media:FOAM,DRY CHEMICA, CO*2, OR WATER (MIST ONLY)

Fire Fighting Procedures:DO NOT USE WATER HOSE.

Unusual Fire/Explosion Hazard:STORAGE IN A HOT AREA WILL DEVELOP PRESSURE IN THE DRUM

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB W/FILTER AID OR DRY INERT POWDER AND SHOVEL UP.

===== Handling and Storage =====

Handling and Storage Precautions:PRODUCT IS FLAMMABLE. DO NOT STORE IN HIGH TEMPERATURE AREAS OR IN AREAS OF FIRE OR OPEN FLAME.

Other Precautions:DO NOT TAKE INTERNALLY. AVOID CONTACT W/SKIN.

===== Exposure Controls/Personal Protection =====

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:WEAR PROTECTIVE COVERALLS TO PROTECT CLOTHING & SKIN

Supplemental Safety and Health

VAPOR DENSITY:HEAVIER THAN AIR. WT PER GALLON:7.94 LS. ADDRESS:P.O. BOX 717, THEODORE, ALABAMA 36582

===== Physical/Chemical Properties =====

HCC:F

4

Boiling Pt:B.P. Text:302-399F

Vapor Pres:2

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:56.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS.

CAUTION:INCINERATION PRODUCES COBALT OXIDE ASH, WHICH SHOULD NOT BE
INHALED. DISPOSE IN ACCORDANCE W/FED, STATE & LOCAL
CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular
situation.