

PRATT AND LAMBERT INC -- FORMULA 117,COMPONENT II,MFR CODE 702701 -- 8030-00-165-8577  
===== Product Identification =====

Product ID:FORMULA 117,COMPONENT II,MFR CODE 702701

MSDS Date:01/01/1985

FSC:8030

NIIN:00-165-8577

MSDS Number: BDDYY

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-

1361

Emergency Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: >50%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:PHOSPHORIC ACID (SARA III)

CAS:7664-38

-2  
RTECS #:TB6300000  
OSHA PEL:1 MG/M3/3 STEL  
ACGIH TLV:1 MG/M3/3 STEL; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:ANESTHETIC,IRRIT OF RESP TRACT,ACUTE CNS  
DEPR-HDACH,DIZZ,STAG.GAIT,CONFUSN,UNCON,COMA.SKIN/EYE IRRIT

===== First Aid Measures =====

First Aid:FLUSH EYES IMMEDIATELY W/WATER FOR 15 MIN.FLUSH SKIN W/WATER  
WHILE REMOVING CONTAMINATED CLOTHING  
.IF INHALED,REMOVE TO FRESH  
AIR. CALL MD IF SUMPTOMS PERSIST.

===== Fire Fighting Measures =====

Flash Point:62F TCC  
Lower Limits:2.50  
Extinguishing Media:CO\*2,DRY CHEM.ALCOHOL FOAM. POLYMER FOAM FOR LARGE  
FIRES.  
Fire Fighting Procedures:IF H\*2O USED FOG NOZZLE PREFERABLE.COOL CLOSD  
CONTNRS W/H2O.  
Unusual Fire/Explosion Hazard:KEEP CONTAINERS CLOSED.ISOLATE FROM  
IGNITION SOURCES. CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE

=====  
= Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT  
SURFACES, & ELECTRICAL,STATIC,OR FRICTIONAL SPARKS). AVOID  
BREATHING VAPORS.VENTILATE AREA. REMOVE W/INERT ABSORBENT &  
NON-SPARKING TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT APPLY TO VERY HOT SURFACES.DO  
NOT STORE ABOVE 120F. STORE LARGE QTYS IN BLDG DESIGNED TO COMPLY  
W/OSHA 1910.106.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.DONT FLAME CUT,BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESPIRATORY PROTECTION FOR EXPOSURE OF CONCERN

Ventilation:PROVIDE GENL DILUTN OR LOCAL EXHAUST TO KEEP TLV BELOW LIMIT

Protective Gloves:YES

Eye Protection:S

FTY EYEWEAR

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

KEY1:F6.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 212F

Vapor Density:>1

Evaporation Rate & Reference: