

KALCOR COATINGS CO., INC -- V-771153-M STAIN,INTERIOR -- 8010-00-165-8627

=====
Product Identification
=====

Product ID:V-771153-M STAIN,INTERIOR

MSDS Date:01/01/1987

FSC:8010

NIIN:00-165-8627

MSDS Number: BDDZF

=== Responsible Party ===

Company Name:KALCOR COATINGS CO., INC

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

CAGE:DO396

=== Contractor Identification ===

Company Name:KALCOR COATING CO

Address:37721 STEVENS BLVD

Box:City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

Phone:216-946-4700

CAGE:33201

Company Name:KALCOR COATINGS COMPANY

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094

Phone:800-424-9300 CHEMTREC

CAGE:DO396

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 44.5%

OSHA PEL:100 PPM

Ingred Name:IRON OXIDE

CAS

:1309-37-1
RTECS #:NO7400000
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

=====
Hazards Identification
=====

Effects of Overexposure:SKIN & EYE IRRITANT. AVOID PROLONGED INHALATION OF VAPORS

=====
First Aid Measures
=====

First Aid:SKIN & EYE:FLUSH IRRITATED AREA W/LG AMT OF WATER. INH:MOVE TO FRESH AIR. (OXYGEN IF NECESSARY)

=====
Fire Fighting Measures
=====

Flash Po
int:105F SCC
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.CLEAN AS ANY PAINT

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT, SPARKS & OPEN FLAME. USE ADEQUATE VETILATION.

=====
Exposure Controls/Personal Protection
=====

Ventilation:LOCAL
VENTILATION NECESSARY
Protective Gloves:RECOMMENDED
Eye Protection:SAFETY GOGGLES/GLASSES
Supplemental Safety and Health
VAP-DENS:HEAVIER THAN AIR.WT PER GAL:8.3 LBS. THIS PRODUCT IS A COMBUSTIBLE LIQUID CLASS II.

=====
Physical/Chemical Properties
=====

HCC:F4
Boiling Pt:B.P. Text:315-385F
Spec Gravity:0.8300
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:VERY FLUID/PAINT
Percent Volatiles by Volume:80.0

=====
Stability and

Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: EXCESS HEAT, SPARKS, OPEN FLAMES

===== Disposal Considerations =====

Waste Disposal Methods: EPA APPROVED LANDFILL OR INCINERATION IF IN ACCORDANCE W/FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of

America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.