

EXXON CO, USA -- AVIATION OIL EE120 -- 9150-00-168-6889

===== Product Identification =====

Product ID:AVIATION OIL EE120

MSDS Date:01/01/1987

FSC:9150

NIIN:00-168-6889

MSDS Number: BDFFJ

=== Responsible Party ===

Company Name:EXXON CO, USA

Address:1251 AVE OF THE AMERICAS

City:NEW YORK

State:NY

ZIP:10020-1104

Country:US

Emergency Phone Num:704-821-9822

CAGE:GO864

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:4N760

Company Name:EXXON CO, USA

Box:2180

CAGE:GO864

Company Name:EXXON COMPANY,USA

Address:1251 AVE OF THE AMERICAS

Box:2180

City:NEW YORK

State:NY

ZIP:10020-1104

Country:US

CAGE:2F871

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBONS

Fraction by Wt: 100%

===== Hazards

Identification =====

Effects of Overexposure:SKIN-PROLONGED/REPEATED CONTACT MAY CAUSE MILD IRRITATION.

===== First Aid Measures =====

First Aid:EYES-FLUSH W/WATER 15 MIN OR UNTIL IRRIT SUBSIDES. SKIN-WASH THOROUGHLY W/SOAP & WATER.

===== Fire Fighting Measures =====

Flash Point:510F/266C/COC

Lower Limits:1

Upper Limits:7

Extinguishing Media:FOAM,DRY CHEM,CARBON DIOXIDE,WATER FOG OR SPRAY

Fire F

ighting Procedures:USE AIR-SUPPLIED BREATHING EQUIP IN ENCLOSE AREAS

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID. ADD ABSORB (SAND,ECT) TO SPILL AREA. KEEP PETROLEUM PRODUCTS OUT OF SEWERS & WATER-COURSES BY DIKING. ADVISE AUTHORITIES IF PRODUCT ENTERS SEWERS,WATERCOURSES OR EXTENSIVE LAND AR EAS

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAIN ERS CLOSED WHEN NOT IN

USE. DO NOT HANDLE OR STORE NEAR HEAT,SPARKS,FLAME OR STRONG OXIDANTS. AVOID BREATHING OIL MIST.

Other Precautions:REMOVE OIL-SOAKES CLOTHING & LAUNDER BEFORE REUSE.

DISCARD OIL-SOAKED SHOES. WASH SKIN THOROUGHLY W/SOAP & WATER AFTER USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AIR-SUPPLIED RESPIR PROTECT IN CONFINED AREAS

Ventilation:LOCAL EXHAUST-PROVIDE >60 FPM FACE VELOCITY IN ENCLOSED ARE

A
Protective Gloves:CHEM RESISTANT
Eye Protection:SPLASH GOGGLES/FACE SHIED
Other Protective Equipment:CHEM RESIST APRON
Supplemental Safety and Health
MIL-L-22851,TYPE II. MSDS DTD 1/86

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:1F,-17C
Vapor Pres: