

J & P PETROLEUM PROD, INC -- TEX-MASTIC #316 ASPHALT PRIMER -- 5610-00-171-4722

=====  
Product Identification  
=====

Product ID:TEX-MASTIC #316 ASPHALT PRIMER

MSDS Date:01/01/1987

FSC:5610

NIIN:00-171-4722

MSDS Number: BDFJX

=== Responsible Party ===

Company Name:J & P PETROLEUM PROD, INC

Emergency Phone Num:214-331-5401

CAGE:4M428

=== Contractor Identification ===

Company Name:J & P PETROLEUM PROD

UCTS INC

Address:2715 S WESTMORELAND STATION A

Box:4206

City:DALLAS

State:TX

ZIP:75208

Country:US

CAGE:4M428

Company Name:MILITARY SPECIFICATIONS PROMULGATED BY MILITARY

Address:DEPTS/AGENCIES UNDER AUTH OF DEF STD

Box:MANUAL

City:4120 3-M

Phone:804-279-4371 DSN 695-4371

CAGE:81349

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ASPHALT CUTBACK

RTECS #:CI9905000

Fraction by Wt: 100%

ACGIH TLV:5MG/CUM FUME

=====  
Hazards Identification  
=====

Effects of Overexposure:DIZZ, PALENESS OF APPEARANCE

=====  
First Aid Measures  
=====

First Aid:GIVE OXYGEN & APPLY NEC CARDIO-PULMONARY ASSISTANCE

=====  
Fire Fighting Measures  
=====

Flash Point:105F, 41C PMCC

Lower Limits:0.7

Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEM

Fire Fighting Procedures:FOAM, CARBON DIOXIDE, DRY CHEM

=====  
Accidental Release Measures  
=====

==

Spill Release Procedures:REMOVE POSS SOURCES OF IGNITION

=====  
Handling and Storage  
=====

Handling and Storage Precautions:NORMAL STG TEMPS OF 50-130DEGF WILL NOT LEAD TO APPRECIABLE FUME BUILDUP, BUT GEN VENT SHOULD BE UTILIZED. FIRE EXTING AVAILABLE.

Other Precautions:KEEP CNTNRS CLOSED WHEN NOT IN USE

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IF MATL IS HEATED, NIOSH APPRVD FULL-FACEPIECE  
O

RGANIC VAPOR

Ventilation:LOCAL EXHST PREFERRED IF MATL IS HEATED

Eye Protection:FACE SHLD OR FULL RESP

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:F4

Boiling Pt:B.P. Text:300F, 149C

Vapor Pres:03

Vapor Density:4.76

Spec Gravity:0.784

Evaporation Rate & Reference:0.16 TO BUT

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK ASPHALT, ASPHALTIC ODOR

Percent Volatiles by Volume:32

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

CARBON MONOXIDE, CARBON DIOXIDE

Stability Condition to Avoid:CLOSED ARES LACKING GENERAL VENT

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing t

his  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.