

BENSON INC. -- BENSON PREMIX TONER -- 6850-00-177-8021

=====  
Product Identification  
=====

Product ID:BENSON PREMIX TONER

MSDS Date:01/01/1987

FSC:6850

NIIN:00-177-8021

MSDS Number: BDFVS

=== Responsible Party ===

Company Name:BENSON INC.

Emergency Phone Num:415 966 9561

CAGE:4X257

=== Contractor Identification ===

Company Name:BENSON INC.

CAGE:4X257

=====  
Composition/Information on Ingre  
dients  
=====

Ingred Name:MIXED ISODECANES

Fraction by Wt: >99%.

ACGIH TLV:300PPM

Ingred Name:CARBON BLACK TREATED WITH AN INSOLUBLE RESINOUS MIXTURE.

Fraction by Wt: 0.5%

=====  
Hazards Identification  
=====

Effects of Overexposure:INHAL:NAUSEA,HEADACHE;FOR MORE SEVERE EXP.MILD  
DEPRESS.&/OR RESP.IRRIT.-INGEST:UPSET STOMACH.,IRRIT.

=====  
First Aid Measures  
=====

First Aid:INHAL:REMOVE TO FRESH AREA.-INGEST:DO

NOT INDUCE VOMIT;CALL

DOCTOR IMMEDIATELY.-EYES:FLUSH WITH WATER FOR 15 MIN.IF

IRRIT.PERSISTS,CALL DOCTOR.

=====  
Fire Fighting Measures  
=====

Flash Point:104.5F,40C,TCC

Lower Limits:0.8

Upper Limits:7.0

Extinguishing Media:FOAM-TYPE EXTINGUISHERS-SUPERIOR TO CO\*2  
EXTINGUISHERS.

Fire Fighting Procedures:AVOID WTR;IT TENDS TO SPREAD HYDROCARBONS  
SOLVENT FIRES.

=====  
Accidental Release Measures  
=====

Spill Release Pro

cedures:REMOVE IGN.SOURCES.IF AMT.IS SMALL(LESS THAN 1 PINT),ALLOW TO EVAP.-IF AMT IS LARGE,TRY TO CONTAIN & SOP UP AS MUCH AS POSSIBLE INTO A CNTNR THAT CAN BE CLOSED.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CNTNRS CLOSED.AVOID STORAGE NEAR HEAT,STRG LIGHT (IF CNTNRS ARE CLEAR),SPARKS,OR OPEN FLAME.

Other Precautions:AVOID USE IN A SMALL CLOSED ROOM OR IN A CONFINED AREA WITH POOR AIR CIRCULATIONS.

=====

= Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:NORMAL AIR CONDITIONING IS ADEQUATE.

Protective Gloves:NONE

Eye Protection:NONE

Other Protective Equipment:NONE

Supplemental Safety and Health

UNDATED MSDS.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt.=166.7C, 332.F

Vapor Pres:99.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRG OXIDANTS

LIKE CHROMIC AC.,LIQ.CHLORINE,CONC.OXYGEN.

Hazardous Decomposition Products:INCOMPLETELY BURNED CARBON PRODUCTS, CO\*2, CO.

===== Disposal Considerations =====

Waste Disposal Methods:LG.CNTNRS OF WASTE MUST BE HANDLED BY PERSONS OR FIRMS WITH FACILITIES FOR DISPOSAL,E.G.,CONTROLLED BURNING.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United

States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.