

DOW CORNING CORP. -- 781 SEALANT -- 8030-00-180-6339

=====
Product Identification
=====

Product ID:781 SEALANT

MSDS Date:01/01/1985

FSC:8030

NIIN:00-180-6339

MSDS Number: BDGDC

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

Z

IP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETOXYSILANE

Fraction by Wt: 5.0%

ACGIH TLV:SEE SUPP DATA

=====
Hazards Identification
=====

Effects of Overexposure:IRRITATES EYES.PROLONGED OR REPEATED CONTACT
MAY IRRITATE

SKIN

=====
First Aid Measures
=====

First Aid:WIPE OFF.FLUSH W/WATER.OBTAIN MEDICAL ATTEN. FOR EYES IF NECESSARY.

=====
Fire Fighting Measures
=====

Flash Point:>250F,121C OC
Extinguishing Media:CO*2 OR FOAM
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APP.& PROTECTIVE CLOTHING
Unusual Fire/Explosion Hazard:NONE KNOWN

=====
Accidental Release Measures
=====

Spill Release P
rocedures:USE ABSORBENT MATERIAL TO COLLECT & CONTAIN FOR SALVAGE OR DISPOSAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE BELOW 90F/32C.USE REASONABLE CARE.
Other Precautions:AVOID CONTACT W.MOIST AIR/WATER BECAUSE ACETIC ACID VAPORS ARE FORMED W/WATER/MOISTURE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:ACID VAPOR TYPE
Ventilation:MECHANICAL(GENERAL)
Protective Gloves:
RUBBER/PLASTIC
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:AS REQD. BY LOCAL AUTHORITIES.
Supplemental Safety and Health
TLV:10 PPM BASED ON LIBERATED ACETIC ACID.

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:>300F,149C
Vapor Pres: