

SHELL OIL COMPANY -- AEROSHELL GREASE 6 -- 9150-00-180-6382

===== Product Identification =====

Product ID:AEROSHELL GREASE 6

MSDS Date:01/04/1999

FSC:9150

NIIN:00-180-6382

MSDS Number: BDGDV

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Address:HEALTH, SAFETY AND ENVIRONMENT

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Country:US

Info Phone Num:713-241-4819/4141/2252 FAX -6511

Emergency Ph

one Num:713-473-9461/800-424-9300(CHEMTREC)

Preparer's Name:G. A. VAN GELDER

CAGE:54527

=== Contractor Identification ===

Company Name:CROWN OIL & CHEMICAL CO.

Address:751 HILL STREET

Box:City:JEFFERSON

State:LA

ZIP:70121

Country:US

Phone:504 OUT OF BUSINESS

CAGE:0CF76

Company Name:EQUILON ENTERPRISES LLC PRODUCT STEWARDSHIP

Address:1111 BAGBY RD RM 4325D

Box:674414

City:HOUSTON

State:TX

ZIP:77267-4414

Country:US

Phone:877-276-7285

CAGE:3N254

Company Name:SHELL OIL COMPANY

Address:Box:2463

Ci

ty:HOUSTON
State:TX
ZIP:77210
Country:US
Phone:800-231-6950
CAGE:54527

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED
(MILD), HEAVY PARAFFINIC
CAS:64742-54-7
RTECS #:PY8035500
Minimum % Wt:85.
Maximum % Wt:90.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:BENTONITE
CAS:1302-78-9
RTECS #:CT9450000
Minimum % Wt:5.
Maximum % Wt:10.
Other REC Limits:NONE RE
COMMENDED
OSHA PEL:5 MG/M3 (DUST)
ACGIH TLV:5 MG/M3 (DUST)

Ingred Name:FATTY ACID AMIDES
CAS:68910-93-0
Minimum % Wt:3.
Maximum % Wt:5.
Other REC Limits:NONE RECOMMENDED

Ingred Name:ADDITIVES
Fraction by Wt: 3-5%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute

and Chronic:ACUTE-EYES:MILD IRRITATION.SKIN:PROLONGED/REPEATED CONTACT MAY CAUSE DERMATITIS,FOLLICULITIS/OIL ACNE.RELEASE DURING HIGH PRESSURE USAGE MAY RESULT IN INJECTION & NECROSIS.INHALATION:VAPORS MAY IRRITATE THE NOSE,THROAT & UPPER RESPIRATORY TRACT.INGESTION:LOW ORDER OF TOXICITY.CHRONIC-MAY CAUSE DERMATITIS.

Explanation of Carcinogenicity:NO DATA PER MSDS

Effects of Overexposure:MILD IRRITATION OF EYES. PROLONGED/REPEATED SKIN CONTACT MAY CAUSE DERMATITIS, FOLLICULITIS/OIL ACNE. RELEASE

DURING HIGH PRESSURE USAGE MAY RESULT IN INJECTION & NECROSIS. INHALATION OF HOT VAPORS MAY IRRITATE THE NOSE, THROAT & UPPER RESPIRATORY TRACT. INGESTION HAS LOW ORDER OF TOXICITY.

Medical Cond Aggravated by Exposure:PREEXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF NEEDED.INHALED:REMOVE TO FRESH AIR.PROVIDE CPR/OXYGEN IF NEEDED.ORAL:DON'T INDUCE VOMITING.NO TREATMENT IS NECESSARY UNLESS LARGE AMOUNT OF PRODUCT IS INGESTED.EYE:FLUSH WITH WATER FOR 15 MINUTES,HOLDING EYELIDS OPEN.SKIN:WIPE EXCESS OFF.WASH WITH SOAP & WATER.NOTE TO PHYSICIAN:IN GENERAL,EMESIS INDUCTION IS UNNECESSARY IN HIGH VISCOSITY,LOW VOLATILITY PRODUCTS,I.E.GREASES,OILS

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC
Flash Point:390F,199C
Extinguishing Media:USE WATER FOG, CO2, OR DRY CHEMICAL. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS

