

BATTENFELD AMERICA INC -- 60,515 DIESEL ENGINE OIL, MIL-L-9000G -- 9150-00-181-8229
===== Product Identification =====

Product ID:60,515 DIESEL ENGINE OIL, MIL-L-9000G

MSDS Date:11/01/1990

FSC:9150

NIIN:00-181-8229

MSDS Number: BDGSK

=== Responsible Party ===

Company Name:BATTENFELD AMERICA INC

Address:1575 CLINTON ST

City:BUFFALO

State:NY

ZIP:14200

Country:US

Info Phone Num:716-822-8410

Emerge

ncy Phone Num:716-822-8410

Preparer's Name:THOMAS MUSILLI

CAGE:61808

=== Contractor Identification ===

Company Name:BATTENFELD AMERICA INC

Address:1575 CLINTON ST

Box:City:BUFFALO

State:NY

ZIP:14206

Country:US

Phone:716-822-8410

CAGE:61808

Company Name:BATTENFELD GREASE AND OIL CORP OF NEW YORK INC

Address:1174 ERIE AVE

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120-3036

Country:US

Phone:716-695-2100

CAGE:60226

===== Composition/Information on Ingredients =====

Ingred Name:D

ISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: 61.7%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:RESIDUAL OILS, HYDROTREATED

CAS:64742-57-0

Fraction by Wt: 25.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:LUBRIZOL 1161 (LUBRIZOL CORP, WICKLIFFE, OH)

Fraction by Wt: 13.3%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MANUFACTURER STATES,"PRODUCT HAS BEEN USED FOR YEARS WITH NO KNOWN ILL EFFECTS. IT CONTAINS NO KNOWN CARCINOGENS OT MUTAGENS AS DEFINED BY OSHA OR IARC." PRODUCT IS VERY MILDLY IRRITATING TO BODY TI SSUES. MOST LIKELY HAZARD IS THAT OF BREATHING THE MIST OR VAPORS S HOULD THE PRODUCT BE HEATED OR MISTED.

Explanation of Carcinogenicity:THE PRODUCT CONTAINS NO INGREDIENT THAT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYE:MILD IRRITATION. SKIN:POSSIBLE MILD IRRITATION. INHALED:RESPIRATORY IRRITATION,POSSIBLE PULMONARY EDEMA IF MIST IS INHALED. INGESTED:NONE GIVEN BY MANUFACTURER (SUPPLIER).

Medical Cond Aggravated by Exposure:NONE REPORTED

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. INHALED:REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. INGESTED:DO NOT INDUCE VOMITING. GIVE 2 LARGE GLASSES OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE,SEE A DOCTOR.

===== Fire Fighting Measures =====

Flash Point

Method:COC

Flash Point:400F,204C

Autoignition Temp:Autoignition Temp Text:450F

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG. WATER, ESPECIALLY STREAM, MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER AS LIQUID IF POSSIBLE. ADSORB REMAINDER ON EARTH,SAND,SAWDUST,ETC. KEEP OUT OF DRAINS, SEWERS, AND WATERWAYS. STORE IN CLOSED CONTAINERS PENDING DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR OR RESPIRATOR FOR OIL MIST IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE.

Ventilation:NORMAL ROOM VENTILATION SHOULD BE SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST IF NEEDED (OIL MIST).

Protective Gloves:NEOPRENE OR BUTYL RUBBER (OIL RESISTANT)

Eye Protection:SAFETY GLASSES

OR SPLASH GOGGLES S

Other Protective Equipment:AS NEEDED TO PREVENT PROLONGED/REPEATED CONTACT.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. MINIMIZE PERSONAL CONTACT. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

MSDS RECEIVED FROM NAVY. NAVY IDENTIFIED NSN. ALSO DOD LABEL WAS SUPPLIED, THIS PROBABLY FILLED OUT BY NAVY.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:700F,371C

Spec Gravity:0

.88

pH:UNKNON

Viscosity:11.9-14.5 CS

Solubility in Water:NEGLIGIBLE

Appearance and Odor:FLUID OIL,BLAND ODOR

Corrosion Rate:N/KNOWN

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE

===== Disposal Considerations =====

Waste Dispo

sal Methods:DISPOSE I/A/W FEDERAL,STATE, LOCAL REGULATIONS.

MFR SUGGESTS RECYCLE OR IF THAT IS NOT PRACTICLE TO INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek compe

tent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.