

DEFT,INC. -- 03GY49 BASE,MIL-C-83286B,GRAY,16473 -- 8010-00-181-8255
===== Product Identification =====

Product ID:03GY49 BASE,MIL-C-83286B,GRAY,16473
MSDS Date:01/01/1987
FSC:8010
NIIN:00-181-8255
Kit Part:Y
MSDS Number: BDGSW
=== Responsible Party ===
Company Name:DEFT,INC.
Address:17451 VON KARMAN AVENUE
City:IRVINE
State:CA
ZIP:92714
Info Phone Num:714-474-0400
Emergency Phone Num:714-474-0400

CAGE:HO407
=== Contractor Identification ===
Company Name:DEFT, INC.
Address:17451 VON KARMAN AVE
City:IRVINE
State:CA
ZIP:92614
Country:US
Phone:949-474-0400
CAGE:33461
Company Name:DEFT,INC.
Address:17451 VON KARMAN AVENUE
Box:City:IRVINE
State:CA
ZIP:92714
Phone:714-474-0400
CAGE:HO407

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 10.0%
OSHA PEL:200 PPM/300 S

TEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)
CAS:111-15-9
RTECS #:KK8225000
Fraction by Wt: 20.0%
OSHA PEL:S,100 PPM
ACGIH TLV:S, 5 PPM; 9192

Ingred Name:ETHYL ACETATE
CAS:141-78-6
RTECS #:AH4250000
Fraction by Wt: 4.0%
OSHA PEL:400PPM
ACGIH TLV:400 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:NON-AQUEOUS SOLUTION,HAZARD UNKNWON,UNIDENTIFIED(% WT BY
DIFFERENCE)
Fraction by Wt: 66.0%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.
Effects of Overexposure:EYES:MODERATE IRRIT;SKIN:IMPOSSIBLE IRRIT BY
SOLVENTS;INH:SOLVENT VAPORS CAN CAUSE IRRIT OR NARCOSIS

=====
===== First Aid Measures =====

First Aid:SKIN:WIPE OFF WITH A RAG THEN THOROUGH
RINSING W/H*20 &
WASHING W/MILD SOAP AND WATER;EYES;FLUSH W/WATER FOR AT LEAST 10
MIN & CONSULT AN EYE PHYSICIAN;INH:REMOVE TO FRESH AIR.GIVE
CPR/OXYGEN IF NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:20F(-6.6C)
Lower Limits:1.6
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG APP H*20 SPRAY TO COOL
CONTR.
Unusual Fire/Explosion Hazard:CAUTIONAGAINST APPLICATION TO HOT SUR

FACES
& USE IN AREAS WHERE SOURCES OF IGNITION MAY BE PRESENT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK.
EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT
ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG
SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

===== Handling and Storage =====

Handling and Storage Precautions:S
TORE IN COOL, DRY, WELL VENT, LOW FIRE
RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT.
KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID PROLONGED INHALATION BO FAPORS.IF VENTILATION
IS POOR,USE A FRESH AIR SUPPLY MASK.DO NOT H*20 STREAM ON FIRE.H*20
SPRAY/FOG CAN BE USED EFFECTVLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA/MESA APPROVD SCBA
Ventilation:LOCAL EXHAUST:USE ADEQUATE VENTILATION WITH
EXHAUST FAN.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR
PROLONGED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. REMOVE
CONTAMINATED CLOTHING.

Supplemental Safety and Health

THIS IS PART A (BASE) OF A 2-PART PRODUCT.PRODUCT IS GRADE A. FOR OLD
PART B FORMULATION,SEE PNI B.FOR NEW PART B FORMULATION,SEE PNI
D,SAME NSN.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-33IF

Vapor Density:>1.0

Spec Gravity:1.3

Evaporation Rate & Reference: