View NSN Online: https://aerobasegroup.kr/nsn/8010-00-181-8284

Product ID:03-BL-48 DEFTHANE MSDS Date:01/01/1985 FSC:8010 NIIN:00-181-8284 Kit Part:Y MSDS Number: BDGTQ === Responsible Party === Company Name: DEFT INC CHEMICAL COATING DIV Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92714-6205 Country:US Info Phone Num:714-474-0400 **Emergency Phone** Num:800-424-9300 CHEMTREC CAGE:33461 === Contractor Identification === Company Name: DEFT, INC. Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92614 Country:US Phone:949-474-0400 CAGE:33461 Ingred Name: ETHYL ACETATE (SARA III) CAS:141-78-6 RTECS #:AH5425000 Fraction by Wt: 20% **OSHA PEL:400 PPM** ACGIH TLV:400 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA

III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 15% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA) CAS:111-15-9 RTECS #:KK8225000 Fraction by Wt: 20% OSHA PEL:S,100 PPM ACGIH TLV:S, 5 PPM; 9192

Effects of Overexposure: MODERATE EYE IRRITANT. POSSIBLE SKIN IRRITANT. INHALATION-IRRITATION OR NARCOSIS

First Aid:SKIN-WIPE WITH CLOTH THEN RINSE WITH WATER & WASH WITH SOAP AND WATER. EYE-FLUSH 10 MIN. WITH WATER. CONSULT PHYSICIAN. INHALATION-REMOVE TO FRESH AIR

Flash Point:28F;-2C TOC Lower Limits:1.6 Extinguishing Media:CO*2,FOAM OR DRY CHEMICAL Fire Fighting Procedures:WEAR RESPIRTOR. DO NOT USE WATER STREAM Unusual Fire/Explosion Hazard:DO NOT APPLY TO HOT SURFACES.DO NOT USE NEAR SPARKS OR OPEN FLAMES

Spill Release Procedures: ABSORB WITH OIL ABSORBING COMPOUND OR DRY RAGS.FLUSH WITH LARGE VOLUME OF WATER.

Handling and Storage Precautions:MATERIA IS MOISTURE SENSITIVE. KEEP IN TIGHTLY CLOSED CONTAINERS

Other Precautions: AVOID PROLONGED INHALATION. IF VENTILATION IS POOR USE FRESH AIR SUPPL Y MASK

Ventilation:LOCAL EXHAUST FAN Protective Gloves:YES Eye Protection:YES Other Protective Equipment:CARTRIDGE TYPE RESPIRTOR-MSC CATALOG NO CR84306 Supplemental Safety and Health B.P.RANGE:79-164C * PART A OF 2 COMPONENT SYSTEM

HCC:F2 Boiling Pt:B.P. Text:175-331F Vapor Pres:26 Vapor Density:>1 Spec Gravity:1.03 Evaporation Rate & amp; Reference:< E THER Solubility in Water:INSOLUBLE Appearance and Odor:BLUE-PAINT;ODOR PLEASANT, PUNGENT Percent Volatiles by Volume:70.9

Stability Indicator/Materials to Avoid:YES WATER, ALCOHOLS AND OTHER COMPOUNDS REACTIVE WITH ISOCYANATE Stability Condition to Avoid:SPARKS, STATIC ELECTRICITY, OPEN FLAME OR HEAT

Waste Disposal Methods:DISPOSE OF IN TIGHTLY CLOSED CO NTAINER AND FINALLY BY SANITARY LANDFILL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.