

WITCO CHEMICAL CORP -- SC 845 3213 , LUBRICATING OIL,ENGINE -- 9150-00-186-6681  
===== Product Identification =====

Product ID:SC 845 3213 , LUBRICATING OIL,ENGINE

MSDS Date:01/01/1987

FSC:9150

NIIN:00-186-6681

MSDS Number: BDHCK

=== Responsible Party ===

Company Name:WITCO CHEMICAL CORP

Emergency Phone Num:(913)782-5800

CAGE:1F469

=== Contractor Identification ===

Company Name:WITCO CHEMICAL CORP

GOLDEN BEAR OIL CO DIVISION

Address:MANOR & NORRIS ROADS

Box:5446

City:OILDALE

State:CA

ZIP:93388-5446

Country:US

Phone:805-393-7110/800-424-9300(CHEMTREC)

CAGE:1F469

Company Name:WITCO CORP

Address:520 MADISON AVE

Box:City:NEW YORK

State:NY

ZIP:10022

Country:US

Phone:212-605-3800

CAGE:82726

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM BASED OIL (PETROLEUM HYDROCARBON),TAKE TLV AS OIL  
MIST =5MG/CUM.

Fraction by Wt: 100%

ACGIH TLV:NOT SPECIFIED

=====  
Hazards Identification  
=====

Effects of Overexposure:MAY CAUSE SKIN AND EYE IRRITATION.PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS.

=====  
First Aid Measures  
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====  
Fire  
Fighting Measures  
=====

Flash Point:340F/171C (COC)  
Extinguishing Media:DRY CHEMICAL,CO\*2,FOAM,WATERFOG,SAND/EARTH  
Fire Fighting Procedures:USE NIOSH APPROVED SCBA IN FIRES, AND CONFINED AREA  
Unusual Fire/Explosion Hazard:MAY FORM DENSE SMOKE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION.ELIMINATE ALL IGNITION SOURCES.DIKE AND CONTAIN;USE ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPO SAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP CONTAINER CLOSED WHEN NOT IN USE.  
Other Precautions:AVOID SKIN AND EYES CONTACT.KEEP OUT OF REACH OF CHILDREN.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS OR OIL MIST.  
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE

ENTILATION

Protective Gloves:RUBBER

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

MSDS DATED 5/03/84

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.896

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID,AMBER OIL,MINERAL OIL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Av

oid:YES

STRONG OXIDIZERS SUCH AS H\*2O\*2,CRO\*3,BROMINE ECT.

Stability Condition to Avoid:OPEN FLAMES,HOT SURFACES, EXTREME HEAT.

Hazardous Decomposition Products:CO AND CO\*2,

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.