

CONTINENTAL OIL CO -- CONOCO FLEET MOTOR OIL, GRADE 40 -- 9150-00-189-6730

=====
Product Identification
=====

Product ID:CONOCO FLEET MOTOR OIL, GRADE 40

MSDS Date:01/01/1985

FSC:9150

NIIN:00-189-6730

MSDS Number: BDHST

=== Responsible Party ===

Company Name:CONTINENTAL OIL CO

Emergency Phone Num:405-767-3456

CAGE:KO523

=== Contractor Identification ===

Company Name:CONOCO INC

Address:1000 S PINE

Box:1267

City:PONCA CITY

State:OK

ZIP:74603

Country:US

Phone:800-441-3637,CHEMTREC 800-424-9300

CAGE:58326

Company Name:CONTINENTAL OIL CO.

CAGE:KO523

=====
Composition/Information on Ingredients
=====

Ingred Name:LUBRICATING OIL

=====
Hazards Identification
=====

Effects of Overexposure:EXCESS INH OF MISTS/VAPORS: PULMONARY DISORDERS. MAY CAUSE EYE IRRIT. SKIN IRRIT POSS.

=====
First Aid Measures
=====

=====

First Aid:EYE: IMMED FLUSH W/WATER AT LEAST 15 MIN, CALL MD. SKIN: WASH THOROUGHLY W/SOAP & WATER. REMOVE CONTAM CLOTHING & WASH BEFORE REUSE. GROSSLY CONTAM LEATHER SHOES SHOULD BE DISCARDED. INGEST: LG AMTS, INDUCE VOMIT, CALL MD. INH: CALL MD!

=====
Fire Fighting Measures
=====

Flash Point:390-440 COC

Extinguishing Media:WATER SPRAY, FOAM, CO*2, DRY CHEM

Fire Fighting Procedures:USE PROPER PROT EQUIP INCL SELF-CNTND BRTHNG APPARATUS

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP PROMPTLY BY ABSORPTION IN CLAY OR EARTH

===== Handling and Storage =====

Handling and Storage Precautions:MAY BE STORED OUTDOORS OR INDOORS AWAY FROM FURNACE OR OTHER HEATING EQUIP

Other Precautions:FOLLOW NEC PRECAUTIONS IAW NFPA CODE 30-1969 FOR COMBUSTIBLE LIQ, CLASS IIIB

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQ

Ventilation:MECH, NORM SHOP VENT

Protective Gloves:NONE REQ

Eye Protection:NONE REQ

Supplemental Safety and Health

VAP PRESS: NIL. SPEC GRAV: 0.86-0.89. MFR STATES PROD NOT CONSIDERED TO BE TOXIC ORALLY OR DERMALLY.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:600F INIT

Evaporation Rate & Reference:NIL

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR BROWN VISCO

US LIQ, SLIGHT ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATLS, HEAT, FLAME

Hazardous Decomposition Products:NORM COMBUST: CO*2, WATER VAPOR.

INCOMP COMBUST: CO.

===== Disposal Considerations =====

Waste Disposal Methods:MFR SUGGESTS CONTROLLED INCINERATION, STORE FOR PROFESSIONAL REMOVAL & DISPOSAL. AVOID DRAINAGE INTO SEWER.DISPOSE

IAW LOCAL, STATE, FED REG.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.