

SULFLO INC. -- VV-G-671E; LUBRICATING GREASE; CODE #1164 -- 9150-00-190-0918

=====  
Product Identification  
=====

Product ID:VV-G-671E; LUBRICATING GREASE; CODE #1164

MSDS Date:01/01/1987

FSC:9150

NIIN:00-190-0918

MSDS Number: BDHVC

=== Responsible Party ===

Company Name:SULFLO INC.

Emergency Phone Num:(716)695-3585

CAGE:JO986

=== Contractor Identification ===

Company Name:SULFLO INC

Address:1158 E

RIE AVE

Box:285

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Country:US

Phone:716-695-3585

CAGE:1V074

Company Name:SULFLO INC.

Address:1158 ERIE AVE

Box:285

City:NORTH TONAWANDA

State:NY

ZIP:14120-3507

Country:US

Phone:716-695-3585

CAGE:JO986

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 85.0%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:CALCIUM STEA

RATE, CAS #1592-23-0  
CAS:1592-23-0  
RTECS #:WI3000000  
Fraction by Wt: 10.0%  
ACGIH TLV:NOT SPECIFIED

Ingred Name:GRAPHITE, CAS #7782-42-5 (TLV =5MG/CUM T.DUST)  
RTECS #:VV7780000  
Fraction by Wt: 5.0%  
ACGIH TLV:2.5MG/CUM R.DST

=====  
Hazards Identification  
=====

Effects of Overexposure:PER MFR,NO KNOWN ILL EFFECTS.MAY IRRITATE EYES,SKIN AND RESPIRATORY TRACT;USE PROPER CARE.

=====  
First Aid Measures  
=====

First Aid:INHAL  
E:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF  
NEED;EYES/SKIN:FLUSH W LG AMTS H\*20 FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

=====  
Fire Fighting Measures  
=====

Flash Point:340F/171C(D-92)  
Autoignition Temp:Autoignition Temp Text:390F  
Extinguishing Media:WATER FOG,CO\*2,DRY CHEMICAL,FOAM,EARTH OR SAND.  
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED  
AREA.

U  
nusual Fire/Explosion Hazard:DO NOT USE WATER DIRECT;WATER MAY CAUSE  
FROTHING.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION:USE SUITABLE  
ABSORBENT MATERIAL LIKE SAND OR INERT MATERIAL AND RECOVER FOR  
PROPER DISPOSAL.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED  
AREA.KEEP AWAY FROM HEAT,SPARKS AND OPEN FLAM

ES;KEEP CONTAINERS  
CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH EYES AND SKIN AND CLOTHES;DO NOT  
USE CONTAMINATED CLOTHES;WASH THOROUGHLY AFTER EACH USE.DO NOT  
BREATHE VAPORS/MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC  
VAPORS/MIST IF > TLV.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE  
VENTILATION

Protective Gloves:NEOPRENE

Eye Protection:GOGGLE

S/FACE SHIELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR  
PROLONGED CONTACT.

Supplemental Safety and Health

MSDS UNDATED.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:700F/371C

Spec Gravity:0.91

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GRAY SEMI-SOLID -BLAND

Percent Volatiles by Volume:0.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STR

ONG OXIDIZERS

Stability Condition to Avoid:HEAT,OPEN SPARKS

Hazardous Decomposition Products:CO AND CO\*2 IF INCOMPLETE COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH  
LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America i

n no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.