

AMERICAN OIL AND SUPPLY CO -- MIL-H-5606E(1) QA, PROD. CODE- 25303 -- 9150-00-223-4134  
===== Product Identification =====

Product ID:MIL-H-5606E(1) QA, PROD. CODE- 25303

MSDS Date:09/01/1990

FSC:9150

NIIN:00-223-4134

MSDS Number: BDKJC

=== Responsible Party ===

Company Name:AMERICAN OIL AND SUPPLY CO

Address:238 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Info Phone Num:201-589-

0263

Emergency Phone Num:201-589-0250

Preparer's Name:LAB MANAGER

CAGE:92895

=== Contractor Identification ===

Company Name:AMERICAN OIL AND SUPPLY CO

Address:239 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Phone:201-589-0250

CAGE:92895

===== Composition/Information on Ingredients =====

Ingred Name:INFORMATION WITHHELD AS A TRADE SECRET. THE PRODUCT IS A  
HYDROTREATED PETROLEUM HYDROCARBON.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:MILD EYE IRRITATION POSSIBLE IN  
ENCLOSED AREAS. MILD SKIN IRRITATION POSSIBLE WITH PROLONGED  
CONTACT.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:EYES: MILD IRRITATION, REDNESS. SKIN: MILD  
IRRITATION, POSSIBLE DERMATITIS, HEADACHE, POSSIBLE UNCONCIOUSNESS.  
INGESTION: NAUSEA, VOMITING, DIARRHEA, GASTROINTESTINAL IRRITATION.

Medical Cond Aggravated

by Exposure:NONE KNOWN

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. GIVENOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Fla  
sh Point Method:PMCC  
Flash Point:200F,93C  
Lower Limits:1.0  
Upper Limits:6.0  
Extinguishing Media:DRY CHEMICAL,FOAM,CARBON DIOXIDE OR WATER FOG  
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS IN ENCLOSED AREA  
Unusual Fire/Explosion Hazard:DO NOT USE DIRECT STREAM OF WATER.MATERIAL MAY FLOAT AND REIGNITE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:RECOVER FREE LIQUID.ADD ABSORBENT TO SPILL AREA.VENTILATE ENCLOSED SPACE  
S.KEEP PETROLEUM PRODUCTS OUT OF STREAMS & WATERWAYS  
Neutralizing Agent:NOT APPLICABLE.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.  
Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VE  
NTILATION. WASH THOROUGHLY AFTER HANDLING.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF > TLV.  
Ventilation:EXHAUST FAN  
Protective Gloves:NEOPRENE  
Eye Protection:SFTY GLASSES,SPLASH SHLD.  
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.  
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMME

NDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR  
FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO  
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres:0.07

Spec Gravity:0.872

Evaporation Rate & Reference: