View NSN Online: https://aerobasegroup.com/nsn/6850-00-224-6663

OCTAGON PROCESS INC. -- MIL-C-372C, CLEANING COMPOUND SOLVENT -- 6850-00-224-6663

Product ID:MIL-C-372C, CLEANING COMPOUND SOLVENT

MSDS Date:06/08/1987

FSC:6850

NIIN:00-224-6663

MSDS Number: BDKKZ === Responsible Party ===

Company Name: OCTAGON PROCESS INC.

Address:596 RIVER ROAD.

City:EDGEWATER

State:NJ ZIP:07020 Country:US

Info Phone Num:201-945-9400

Emergency Ph

one Num:201-945-9400

CAGE:82925

=== Contractor Identification ===

Company Name: AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

Company Name: OCTAGON PROCESS INC.

Address:596 RIVER ROAD Box:City:EDGEWATER

State:NJ ZIP:07020 Country:US

Phone:201-945-9400

CAGE:82925


====== Composition/Information on Ingredients ========

Ingred Name: PETROLEUM HYDROCARBON

ACGIH TLV:5MG/CUM (OIL MI

Ingred Name:UNIDENTIFIED COMPONENTS (ADDITIVES) ACGIH TLV:NOT SPECIFIED
=========== Hazards Identification ============
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:ACUTE: IRRITATING TO SKIN, EYES, & MUCOUS MEMBRANES. OVEREXPOSURE XAN CAUSE 'CNS' DEPRESSION. Effects of Overexposure:EYES: STINGING SENSATION TO EYES; SKIN: REDNESS OF SKIN; INHAL:'CNA' DEPRESSION EVIDENCED BY HEADACFHE, DIZZINESS LOSS OF APPETITE, LOSS OF COORDINATION Medical Cond Aggravated by Exposure:NO DATA AVAILABLE
======================================
E' A' LEVEQ/OWN, ELLIQUIAMANATED EOD AT LEAGT 45 MINO, OFT MEDICAL
First Aid:EYES/SKIN: FLUSH W/WATER FOR AT LEAST 15 MINS. GET MEDICAL ATTN. IF IRRITATION PERSISTS; INHAL: EREMOVE TO FRESH AIR. TREAT SYMPTOMATICALLY; INGEST: ACCIDENT INGESTION- DO NOT INDUCE VOMITING. GET IMM EDIATE MEDICAL ATTN.
======================================
Flash Point Method:PMCC Flash Point:1 52F/67C Lower Limits:0.7 Upper Limits:5.0
Extinguishing Media:FOAM,CO*2,DRY CHEMICAL,OR WATER FOG OR SPRAY. Fire Fighting Procedures:NORMAL.KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER
Unusual Fire/Explosion Hazard:MODERATE WHEN EXPOSED TO HEAT AND FLAME.
========= Accidental Release Measures =========
Spill Release Procedures:DIKE AREA.SHUT OFF IGNITION SOURCES.RECOVER

CAN BE VACUUMED UP & RECOVE



HCC:V4

Boiling Pt:B.P. Text:338F/170C Vapor Density:4.5 Spec Gravity:0.9 Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR LIQ,SLIGHT OILY ODOR

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous Decomposition Products: INCOMPLETELY BURNED CARBON PRODUCTS
CO*2, CO.

======= Disposal Considerations ============

Stability and Reactivity Data =========

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (p

rovided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.