

PERMAGILE-SOLMON LTD -- PG-2125,PART B -- 8030-00-227-1698

=====  
Product Identification  
=====

Product ID:PG-2125,PART B

MSDS Date:01/01/1985

FSC:8030

NIIN:00-227-1698

MSDS Number: BDKTJ

=== Responsible Party ===

Company Name:PERMAGILE-SOLMON LTD

Emergency Phone Num:516-349-1100

CAGE:KO067

=== Contractor Identification ===

Company Name:PERMAGILE INDUSTRIES INC

Address:101 COMMERCIAL STREET

City:PL

AINVIEW

State:NY

ZIP:11803

Country:US

Phone:516-349-1100/800-424-9300(CHEMTREC)

CAGE:13549

Company Name:PERMAGILE-SOLMON LTD

CAGE:KO067

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 2%

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

Ingred Name:GLYCERIN

CAS:56-81-5

RTECS #:MA8050000

Fraction by Wt: 3%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 (MIST) 9293

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000  
Fraction by Wt: 4.5%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 5%  
OSHA PEL:400 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:2,4,6 TRI (DIMETHYLAMINO METHYL) PHENOL  
CAS:90-72-2  
RTECS #:SN3500000  
Fraction by Wt: 14%

=====  
Hazards Identification  
=====

Effects of Overexposure:EYE/SKIN: IRRITATION.  
VAPORS: HEADACHE,DIZZNESS

=====  
First Aid Measures  
=====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES,GET MEDICAL ATTN. SKIN:  
REMOVE CONTAMINATED CLOTHING & WASH AFFECTED AREA WITH SOAP &  
WATER, INHALATION: REMOVE FROM EXPOSURE.

=====  
Fire Fighting Measures  
=====

Flash Point:>200F/93C (COC)  
Extinguishing Media:CO\*2,DRY CHEMICAL,WATER FOG,FOAM.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ABSORB SPILLAGE WITH RAGS,SAWDUST OR SAND.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT AND OPEN FLAME.  
USE ONLY WITH ADEQUATE VENTILATION.  
Other Precautions:AVOID BRATHING VAPORS AND EYE/SKIN CONTACT.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN.  
Ventilation:LOCAL/MECHANICAL

Protective Gloves:RUBBER/PLASTIC

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:COVERALLS OR APRON.

Supplemental Safety and Health

ADD INGREDIENTS:FUMED SILICA,3%;MAGNESIUM SILICATE,28%;POLYAMIDE  
RESIN,39%;IRON OXIDE BLACK,1.5%. PART B OF A TWO PART KIT.

CONTAINER SIZE: 1 GAL. TYPE 1.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.18

Evaporation Rate & Reference: