

PENRECO, DIV OF PENNZOIL CO -- PETROTECT IX,MIL-C-16173,GRADE 1 -- 8030-00-231-2345

=====
Product Identification
=====

Product ID:PETROTECT IX,MIL-C-16173,GRADE 1
MSDS Date:01/01/1985
FSC:8030
NIIN:00-231-2345
MSDS Number: BDKXQ
=== Responsible Party ===
Company Name:PENRECO, DIV OF PENNZOIL CO
Address:700 MILIAM ST
Box:2967
City:HOUSTON
State:TX
ZIP:77252
Country:US
Info Phone Num:800-245-3952

E
mergency Phone Num:800-245-3952
CAGE:86459
=== Contractor Identification ===
Company Name:PENRECO, DIV OF PENNZOIL CO
Address:700 MILIAM ST
Box:2967
City:HOUSTON
State:TX
ZIP:77252
Country:US
Phone:800-245-3952
CAGE:86459

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 37%
OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexp

osure:EYE: BURN/IRRIT. SKIN: IRRIT. VAPORS:
IRRIT,DROWSINESS,PNEUMONIA,COMA. INGESTION: IRRIT GI TRACT

=====
First Aid Measures
=====

First Aid:EYE: FLUSH WITH WATER 15 MIN,CALL PHYSICIAN. SKIN: WASH WITH
SOAP & WATER,REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE TO
FRESH AIR,GIVE ARTIF RESP IF NEEDED,CALL MD. INGESTION: DO NOT
INDUCE VOMI TING,CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash
Point:100F/37C (PMCC)
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE
Fire Fighting Procedures:TREAT AS AN OIL FIRE,WATER ONLY TO COOL
EXPOSED CONTAINERS
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHEN
BURNING,SOLVENT CAN CREATE MODERATE FIRE OR EXPLOSION HAZARD

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE FROM IGNITION SOURCES,SCRAPE MATERIAL
INTO WASTE CONTAINERS,OR ABSORB WITH DRY SAND OR OIL ABSORBENTS
.
CLEAN SPILL AREA WITH DETERGENT SOLUTIONS OR SAFETY SOLVENTS.
PROVIDE ADEQUATE VENTILATION DURING CLEAN UP.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN SEALED CONTAINERS AWAY FROM
HEAT,OPEN FLAME,AND OXIDIZING MATERIALS.
Other Precautions:FIRE EXTINGUISHERS MUST BE KEPT READLY AVAILABLE &
PERSONNEL TRAINED IN PROPER USE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protecti
on:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:LOCAL/GENERAL
Protective Gloves:RUBBER,SYNTHETI
Eye Protection:SPLASH PROOF GOGGLES
Other Protective Equipment:RUBBER PROTECTIVE CLOTHING,BOOTS,APRONS
Supplemental Safety and Health
50% DISTILLATION TEMPERATURE IS BETWEEN 300-360F. PKG: 1 GAL.SOLVENT
CONTAINS NO DETECTABLE BENZENE (IE: