

ASHLAND CO. -- TECTYL 802-A -- 9150-00-231-2361

=====
Product Identification
=====

Product ID:TECTYL 802-A

MSDS Date:01/01/1985

FSC:9150

NIIN:00-231-2361

MSDS Number: BDKYT

=== Responsible Party ===

Company Name:ASHLAND CO.

Emergency Phone Num:606-324-1133

CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Coun

try:US

Phone:800-622-6846

CAGE:81355

=====
Composition/Information on Ingredients
=====

Ingred Name:100 PALE OIL(30-60 %)

Fraction by Wt: 60.0%

ACGIH TLV:SMG/CUM.

Ingred Name:2000 PALE OIL(30-60 %)

Fraction by Wt: 30.0%

ACGIH TLV:SMG/CUM

=====
Hazards Identification
=====

Effects of Overexposure:EYES:SEVERE IRRIT.SKIN:MOD.IRRIT.INHAL:NASAL &
RESP. IRRIT.INGEST:GI IRRIT,VOM

=====
First Aid Measures
=====

=====

First Aid:SKIN:WASH W/SOAP & WATER.REMOVE CONT.CLTHG.EYES:FLUSH W/WATER.SEE DR.INGEST:GIVE 2 GLASSES OF WATER;INDUCE VOMITING; CALL DR.INHAL:MOVE TO FRESH AIR.IF NECESSARY RESTORE BREATHING.

===== Fire Fighting Measures =====

Flash Point:>200F CC
Lower Limits:0.80
Extinguishing Media:DRY CHEMICAL,CO*2
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS W/FULL FACEPIECE,POS.PSI.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL:ABSORB LIQUID ON PAPER,VERMICULITE,FLOOR ABSORB. ALLOW TO EVAPORATE.ELIMINATE ALL SOURCES OF IGNIT.LARGE SPILL:STOP SPILL AT SOURCE,DIKE AREA,ELIMINATE ALL IGN.SOURCES.REMAINING LIQ.TAKEN UP ON SAND,CLAY,EARTH,FLOOR ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS MAY BE HAZARDOUS WHEN EMPTIED.SINCE EMPTIED CONTAINERS CONTAIN PRODUCT RESIDUES.(VAPOR,LIQUID,&/OR SOLID)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOISH/MESA JOINTLY APPD SELF-CONTAINDE BREATHING APPAR.W/FULL FACE P
Ventilation:SUFFICIENT MECHANICAL(GEN) &/OR LOCAL EXHAUST TO MAINT.LTLV
Protective Gloves:BUNA-N,NEOPRENE
Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment:WEAR IMPERVIONS CLOTHING & BOOTS.
Supplemental Safety and Health
SPECIAL FIREFIGHTING PROCEDURES(CONTD):

WATER OR FOAM MAY CAUSE FROTHING
WHICH CAN BE VIOLENT & POSSIBLY ENDANGER LIFE OF THE FIREFIGHTER.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:560F

Vapor Pres:1.0

Spec Gravity: