

DOMINION CHEMICAL COMPANY -- O-S-801,SULFURIC ACID,ELECTROLYTE,CL 4
6810-00-236-0702

=====
Product Identification
=====

Product ID:O-S-801,SULFURIC ACID,ELECTROLYTE,CL 4

MSDS Date:01/01/1985

FSC:6810

NIIN:00-236-0702

MSDS Number: BDLSF

=== Responsible Party ===

Company Name:DOMINION CHEMICAL COMPANY

Address:PUDDLEDOCK RD

Box:1069

City:PETERSBURG

State:VA

ZIP:23803

Country:US

CAGE:9A273

=== Cont

actor Identification ===

Company Name:DOMINION CHEMICAL CO

Address:2050 PUDDLEDOCK RD

Box:1069

City:PETERSBURG

State:VA

ZIP:23803

Country:US

Phone:804-733-7628

CAGE:9A273

=====
Composition/Information on Ingredients
=====

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000

Fraction by Wt: 28.3%

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Routes of E

ntry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:SKIN IRRITANT. SEVERE DAMAGE MAY OCCUR IF
INDUCED INTO HUMAN EYES.

=====
===== First Aid Measures =====

First Aid:IRRIGATE EYES WITH WATER. WASH CONTAMINATED AREA OF BODY WITH SOAP AND WATER. STOMACH WASH IF SWALLOWED. OXYGEN WITH USE OF INTERMITTENT POSITIVE PRESSURE BREATHING APPARATUS. 5% SOLUTION OF SODIUM BI CARBONATE AS A
EROSOL MAY BE USED, AS WELL AS
DECONGESTANT.

=====
===== Fire Fighting Measures =====

Extinguishing Media:SUITABLE DRY CHEMICAL. USE WATER WITH CARE. AVOID SPLATTERING.

=====
===== Accidental Release Measures =====

Spill Release Procedures:COVER WITH SODIUM CARBONATE OR AN EQUAL MIXTURE OF SODA ASH AND SLAKED LIME. AFTER MIXING, ADD WATER IF NECESSARY TO FORM A SLURRY.
Neutralizing Agent:SODA ASH OR LIME

=====
===== Handling and Storage =====

Handling and Storage Precautions:PROTECT AGAINST PHYSICAL DAMAGE. SEPARATE FROM CARBIDES, CHLORATES, FULMINATES, NITRATES, PICRATES, POWDERD METALS.
Other Precautions:PREVENT CONTACT WITH WATER. AVOID CONTACT WITH COMBUSTIBLES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:CHEMICAL CARTRIDGE RESPIRATOR
Ventilation:GENERAL
Protective Gloves:RUBBER
Eye Protection:SAFETY GOGGLES
Other Protecti

ve Equipment:RUBBER BOOTS.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:C1

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

METALS, SULFIDES

Stability Condition to Avoid:HIGH HEAT, MOISTURE

Hazardous Decomposition Products:OXIDES OF SULFUR, HYDROGEN SUL

FIDE,

HYDROGEN GAS

===== Disposal Considerations =====

Waste Disposal Methods:ADD SLOWLY TO A LARGE AMOUNT OF SOLUTION OF SODA ASH AND SLAKED LIME BY STIRRING. DISCHARGE SOLUTION INTO APPROVED STORAGE CONTAINER FOR CORROSIVES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or im

plied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.