

STEVEN INDUSTRIES (ASHLAND OIL CO.,INC.DUBLIN,OHIO -- TECTYL 502C -- 8030-00-244-1295

=====
Product Identification
=====

Product ID:TECTYL 502C

MSDS Date:01/01/1987

FSC:8030

NIIN:00-244-1295

MSDS Number: BDNBB

=== Responsible Party ===

Company Name:STEVEN INDUSTRIES (ASHLAND OIL CO.,INC.DUBLIN,OHIO

Emergency Phone Num:614-790-3333

CAGE:33150

=== Contractor Identification ===

Company Name:STEVEN I

NDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS

ACGIH TLV:500 PPM

Ingred Name:PETROLUEM HYDROCARBONS

=====
Hazards Identification
=====

Effects of Overexposure:EYE,SKIN

IRRITANT;NAUSEA,DIZZINESS,VOMITING,HEADACHE

=====
First Aid Measures
=====

First Aid:WASH SK

IN WITH SOAP AND WATER;FLUSH EYES 15 MINUTES WITH WATER.DO NOT INDUCE VOMITING;CALL DOCTOR

=====
Fire Fighting Measures
=====

Lower Limits:0.8

Upper Limits:5.0

Extinguishing Media:CARBON DIOXIDE,FOAM,DRY CHEMICAL

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCES,STOP SPILL AT SOURCE,CONTAIN SPILL BY DIKE;PUMP INTO SALVAGE TANK

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID EYE AND SKIN CONTACT,BREATHING VAPORS;WASH AFTER HANDLING

=====
Exposure Controls/Personal Protection
=====

Ventilation:TO MAINTAIN TLV

Protective Gloves:LONG GLOVES

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:N1

Boiling Pt:B.P. Text:310F;154.4C

Vapor Density:>1

Evaporation Rate & Reference: