View NSN Online: https://aerobasegroup.kr/nsn/6810-00-245-6695

Product ID: ETHYL ACETATE AR MSDS Date:01/01/1987 FSC:6810 NIIN:00-245-6695 **MSDS Number: BDNFV** === Responsible Party === Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION Address: PARIS BYPASS Box:M City:PARIS State:KY ZIP:40361 Country:US Info Phone Num:314-982-5000 Emergenc y Phone Num:314-982-5000 CAGE:62910 === Contractor Identification === Company Name: MALLINCKRODT SPECIALTY CHEMICALS CO Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:908-859-2151 CAGE:62910 Ingred Name: ETHYL ACETATE (SARA III) CAS:141-78-6 RTECS #:AH5425000 Fraction by Wt: >99% OSHA PEL:400 PPM ACGIH TLV:400 PPM; 9192 EPA Rpt Qty:5000 LBS

=========== Haz

DOT Rpt Qty:5000 LBS

## Effects of Overexposure:INH:IRRITNT TO NOSE/RESP TRCT;ING:CAUSES DIARRHEA,SORE THROAT;SKIN:DEFATS,IRRIT,EYES:IRRITATION.

First Aid:INHAL:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED;INGEST:IF SWALLOWED,GIVE TWO GLASSES OF WATER & INDUCE VOMIT.NOTHING BY MOUTH IF UNCON;SKIN/EYE EXPOSURE:RMV CONTMNTD CLOTHG.WASH SKIN W/SOAP & H\*20 .FLUSH SKIN/EYES W/LG H\*20;GET MED HE LPIMMEDIATLY

Flash Point Method:CC Flash Point:=-4.4C, 24.F Autoignition Temp:=427.C, 800.6F Lower Limits:2.2 Upper Limits:11.0 Extinguishing Media:DRY CHEMICALS,FOAM,CO\*2;WATER SPRAY TO KEEP EXPOSD CANS COOL Fire Fighting Procedures:USE H\*20 TO COOL EXPD CONTRS. USE SCBA & FULL PROT.CLTHG. Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE EXPLOSIVE WITHIN FLAMMABLE LIMITS;AUTO IGN TEMP:427C(800 F)

Spill Release Procedures:RMV IGN SOURCES.VENT AREA.USE RESP PROTCTION & PROTCTV CLOTHG.KEEP OUT OF SURF H\*20,SEWRS/CONFND AREAS;SM SPILL:ABSORB W/PAPER TOWELS.EVVAP UNDER FUME HOOD THEN BURN CAREFULLY;LG SPILL:DIKE AREA.CONTA IN & RECOVER SPILL IF POSS;SHOVL RESDUEINTO DRUMS

Handling and Storage Precautions: PROTCT AGAINST PHYSICAL DAMAGE.S TORE

IN COOL, DRY WELL VNTLTD AREA AWAY FM ING/HEAT SOURCES, OXIDZG MATL.OUTSIDE OR DETACHED SORAGE IS PREFERRED.

Other Precautions:KEEP AWAY FROM HEAT,SPARKS,FLAMES.KEEP CONTNRS CLOSED.USE W/ADEQUATE VENT.AVOID BRTHG DUST.WASH THOROUGHLY AFTER HNDLG.VOND/GROUND CONTNRS WHEN TRNSFRG MATERL.USE NON-SPARKG TYPE TOOL & EQUIP.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection: FULL FACE RESPIRATOR Ventilation: LOCAL EXHAUST TO MAINTN BELOW T LV. Protective Gloves: IMPERVIOUS Eye Protection: GOGGLES/FACE SHIELD Other Protective Equipment: FULL PROTECTIVE CLOTHING, SAFETY SHOWER, EYE WASH STATION Supplemental Safety and Health MSDS FM MR DATED:22 AUG 85, CONFORMS TO OSHA HAZ COMM STD. HCC:F2 NRC/State Lic Num:NOT RELEVANT Boiling Pt:=77.2C, 171.F Vapor Pres:76 Vapor Density:3.0 Spec Gravity:0.9 Evaporation Rate & amp; Reference:6(BUT ACETATE=1) Solubility in Water:MOD ERATE Appearance and Odor: COLORLESS LIQUID. PLEASANT FRUITY ODOR. Percent Volatiles by Volume:100 Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS, STRONG ALKALIES/ACIDS.NITRATES. Stability Condition to Avoid:HEAT, IGNITION SOURCES Hazardous Decomposition Products:CO, CO\*2 WHEN HEATED TO DECOMPOSITION Conditions to Avoid Polymerization:HEAT WILL CONTRIBUTE TO INSTBLTY.SLOWLY DECOMPOSED BY MOISTR \_\_\_\_\_ Waste Disposal Methods: LG SPILL & LOT SIZES OF HAZ WASTE CAN BE ATOMIZED IN A RCRA APPRVD COMBUSTION CHAMBER OR DISPOSED OF IN A RCRA APROVED LAND FILL FACILITY.DO NOT FLUSH TO SEWER.ENSURE COMPLIANCE W/FED, STATE, & LOCAL R EGS; REPORTABLE QTY (RQ)(CWA/CERCLA);5000LBS Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The Un

ited States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.